

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3, 4, 9 and 10

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W.H. Byars, under contract # 420 survey dated Sept. 16 1881 (DCSO records Vol. 20 Page(s) 8680-81)

- 
- Set a Cedar post 4 ft. long, 4" sq., 24" in the ground, for cor. to secs. 3, 4, 9 and 10, marked T32S R6W S3 on NE.; S10 on SE.; S9 on SW.; and S4 on NW. faces, with 5 notches on S. and 3 notches on E. edges, from which
- A Laurel 11" dia., bears N.65°E., 43 lks. dist., mkd. T32S R6W S3 BT.
  - A Fir 36" dia., bears S.66°E., 47 lks. dist., mkd. T32S R6W S10 BT.
  - A Laurel 16" dia., bears S.65°W., 7 lks. dist., mkd. T32S R6W S9 BT.
  - A Fir 50" dia., bears N.45°W., 111 lks. dist., mkd. T32S R6W S4 BT.

Survey by L.V. Swearingen - For: Robert Dollar Co. - 1960-63 - C.S. File 51/68-7

- 
- Found - Orig. 36" Fir S.66°E., 47 lks., has been blown over and logged. After the tree was cut into logs, the stump tipped back upright leaving a stump approx. 10 ft. tall. Orig. bark scribing is plainly visible on the stump.
- Orig. 50" Fir N.45°W., 111 lks. is still standing but will probably be cut in the near future. Orig. bark scribing on this tree has practically disappeared.
- Other two original BTs are gone.
- Marked the corner with a 7/8" x 30" hex drill steel driven 20" in the ground.
- New BTs -8" Incense Cedar S.57°E., 66.5 ft. scribed S9 R4186 BT.
- 4" Tan Oak N.29½°E., 15.0 ft. scribed S3 R4186 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, Joe Brady, crew - Sept. 1967 - C.S. File 54/53-3

- 
- Found - Orig. 36" D.Fir now a 48" stump, S.66°E., 31.0 ft. bark scribe visible, 2S R6W S
- Orig. 50" now 52" bark scribe visible "T R6".
- Iron rod at sec. corner.
- 8" TanOak N.27°E., 15.4 ft. mkd. S3 R4186 BT.
- 10" Cedar stob S.57°E., (found to be S.7°W.) 66.5 ft. scribed R4186.

(Cont. Next Page)

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Sec. cor. for 3, 4, 9 and 10

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Set Brass cap at cor. mkd: County Surveyors Office  
T 32 S R 6 W  
S 4 | S 3  
S 9 | S 10  
1967

New BTs -6" Chinquapin N.17°W., 20.8 ft. mkd. T32S R6W S4 CS  
BT.  
12" Laurel S.10°W., 72.8 ft. mkd. T32S R6W S9 CS BT.  
This corner lies in cut over area approx. 460.0 ft. W. of  
ridge top, running about N-S.

David Edwards - For: Swanson Group, Inc. - 10/2003 - M 143-23  
-----  
Found - Brass cap  
14" Tan Oak N.27°E., 15.4 ft.  
17" Laurel S.10°W., 72.8 ft.  
New BTs- 6" Cedar S.40°E., 16.0 ft. "S 10 BT"  
12" Fir N.37°W., 8.3 ft. "S 4 BT"