

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 400640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, under contract # 420 survey dated Sept. 16 1881 (DCSO records Vol. 20 Page(s) 8682)

Set a Cedar post 3" sq., 3 ft. long, 24" in the ground, for 1/4 sec. cor. marked 1/4 S on W. face, from which
A Fir 16" dia., bears S.82°E., 9 lks. dist. mkd. 1/4 S BT
A Fir 36" dia., bears N.70°W., 25 lks. dist. mkd. 1/4 S BT

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, Joe Brady, crew - Sept. 1967 - C.S. File 54/53-1

Found - Orig. 36" now 42" D.Fir N.70°W., 16.5 ft. faint bark scribe visible, 1/4 S
Orig. 16" D.Fir now rotten stump S.82°E., 5.9 ft.
Set Brass cap at cor. mkd: County Surveyors Office
T 32 S R 6 W
1/4 S 4 | S 3
1967

New BTs -12" D.Fir N.31°W., 16.7 ft. mkd. 1/4 S4 CS BT.
8" Yewwood S.34°E., 23.7 ft. mkd. 1/4 S3 CS BT.

Note - This cor. lies approx. 55.0 north of small creek.

Fd. OK, Feb. 1985, O. Frederick, M 90-67; C.S. File 63/11

Cor. Fd. and used in BLM Subdivision of sec. survey by Dixon and Hartley, Cadastral Surveyors, under Group #1337, surveyed July/Sept. 1989 (DCSO records Vol. 48 Page 18582)