

PRIMARY CORNER DESCRIPTION C C for Secs. 3 & 4 only

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

<p>GLO survey by George W. Hyde and Charles H. Gardner, Deputy Surveyors, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8637)</p> <p>-----</p> <p>Set post, cor. to secs. 3 and 4, T33S R6W, from which A W.Fir 30" dia., bears S.47°E., 55 lks. dist. A W.Fir 30" dia., bears S.45°W., 82 lks. dist.</p>
<p>Cor. Fd. and used in survey for H.E. Cliff, Nov. 20, 1873, Field Book 97 Page 30</p>
<p>Survey by Ronald A. Brandt - For: Robert Dollar Co. - May 1973 - C.S. File 55/294 and M 49-21</p> <p>-----</p> <p>Set 1" x 60" I.Rod, 12" deep, from which bears 1" x 36" I.Rod 4" high, N.61°32'27"W., 22.96 ft. at South side of small cherry tree. 1" x 36" I.Rod 4" high, N.44°15'33"E., 56.26 ft. at South side of a cedar fence post. 1" I.Pipe, 15" deep, N.89°30'59"W., 209.68 ft. set by Nelson, 1933.</p>
<p>Gerald Nygren - 11/23/94 - M 121-31</p> <p>-----</p> <p>Monument FD. - 1" I.R., 20" deep in field NE of Sethers barn said 1" I.R., bears N.05°12'07"W., 1.45' from computer cor. position.</p>
<p>Raymond Wytcherley - For: Misty Morningstar - 7/2001 - C.S. File 65/38-3E - M 137-18</p> <p>-----</p> <p>Set - 5/8" I.Rod W/Yel. plastic cap 8" below surface, from which existing steel fence posts, measured to center of base of posts, on which I set BT signs: A steel fence post bears S.8°52'W., 132.4 ft. A steel fence post bears N.65°36'E., 81.2 ft. A steel fence post bears N.3°12'W., 29.6 ft. A 1" I.Rod per Brandt bears N.0°32'W., 1.45 ft.</p>
<p>BLM Dependent resurvey by Richard J. Dieckmann, Cadastral Surveyor, Group No. 2125, surveyed July 2006/Feb. 2007 - (DCSO records Vol. 55 Page(s) 21448)</p> <p>-----</p> <p>The ¼ sec. cor. of sec. 34 only, the standard sec. cor. of secs. 3 and 4, on the N. bdy. of T33S R6W reestablished by proportionate measurement, by Wytcherley, in 2001, bears N.89°44'50"W., 2453.28 ft., continued next page</p>

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 403100

PRIMARY CORNER DESCRIPTION C C for Secs. 3 & 4 only;

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

there is no remaining evidence of the original cor.; this position was verified and is accepted as the cor.; monumented with an iron rod, 5/8" dia., firmly set, buried 7" below the ground, with plastic yellow cap mkd. WYTCHERLEY LS 2724, from which accessories reported by Wytcherley

A "T" iron fence post, bears N.65½°E., 81.2 ft.

A "T" iron fence post, bears S.8¾°W., 132.2 ft.

A "T" iron fence post, bears N.3¼°W., 29.6 ft.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 43" in the ground, top 15" below surface, directly over the iron rod, with brass cap mkd.

S 4 | S 3
T33S R6W
SC
2006

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From the standard sec. cor. of secs. 3 & 4, T33S R6W a point established as this same cor. by Brandt, in 1973, bears N.1°31'W., 1.40 ft., monumented with an iron rod, 1" dia., buried 12" below the ground, and was not used for control in this survey.