

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 440100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. Sec. 34 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by George W. Hyde and Charles H. Gardner, Deputy Surveyors, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8641)

-----  
Set ¼ sec. post, from which  
A Fir 3" dia., bears N.65°E., 20 lks. dist.  
A Willow 3" dia., bears N.25°W., 19 lks. dist.

Survey by W.H. Lawrence - Sept. 13, 1955 - C.S. File 42/327

-----  
Set 1" galv. iron pipe, 36" long, driven 24" into ground, from which  
Ash 1 ft. diam. bears N.4°E., 111.3 ft.  
Ash 1 ft. diam. bears N.51°W., 72.7 ft. mkd. ¼ S34 BT 1543  
Ran the South side of the sec placing the ¼ cor. at midpoint.

Fd. Cor. OK, DCSO, John Powell, Oct. 5, 1967, C.S. File 54/53-18

Raymond Wytcherley - For: Misty Morningstar - 7/2001 - C.S. File 65/38-3E - M 137-18

-----  
Set - 5/8" I.Rod w/Yel. plastic cap 8" below surface, from which, existing steel fence posts, measured to center of base of post, on which I set BT signs:  
A steel fence post bears S.74°44'W., 132.26 ft.  
A steel fence post bears N.62°19'W., 62.97 ft.  
A 1½" I.Pipe per C.S. 42/327 bears N.40°08'E., 4.09 ft.  
A 5/8" I.Rod per M121-31 bears S.89°39'54"E. 198.71 ft.

BLM Dependent resurvey by Richard J. Dieckmann, Cadastral Surveyor, Group No. 2125, surveyed July 2006/Feb. 2007 - (DCSO records Vol. 55 Page(s) 21446-7)

-----  
The ¼ sec. cor. of sec. 34 only, on the S. bdy. of the Tp., established by proportionate measurement, by Lawrence, in 1955, there is no remaining evidence of the original corner; this position was verified and is accepted as the cor. monumented with a severed iron pipe, 1½" dia., firmly set, projecting 1 in. above the ground.

At the corner point  
Set a stainless steel post, 28" long, 2½" dia., 29" in the ground, top 1" below surface, directly over the iron pipe, with brass cap mkd.

T32S R6W  
¼ S 34  
T33S R6W  
2006

from which

continued next page

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 440100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. Sec. 34 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

An ash, 17" dia., bears N.21¼°E., 148.8 ft., not marked at the request of the landowner.

A utility pole, No. PPL E4469, bears S.60¼°W., 218.2 ft.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this corner, a point established as the ¼ sec. cor. of sec. 34 by Wytcherley, in 2001, bears S.41°30'W., 4.0 ft. dist., monumented with an iron rod, 5/8 in. diam., firmly set, buried 10 ins. below the ground, with plastic yellow cap mkd. WYTCHERLEY LS 2724, and was not used for control in this resurvey.