

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Section 34

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Survey by H.W. Lawrence - For: Carl and Olger Sether - Sept. 1955 - C.S. File 42/327

Drove galv. Iron pipe for center 1/4 corner.

Raymond Wytcherley - For: Misty Morningstar - 7/2001 - C.S. File 65/38-3C - M 137-18

Set - 5/8" I.Rod w/Yel. plastic cap from which:
A Fir 8" dia., bears N.15°W., 48.3 ft. scribed "C¼ BT"
A Fir 10" dia., bears S.45°W., 30.0 ft. scribed "C¼ BT"
A Fir 12" dia., bears S.44°E., 31.7 ft. scribed "C¼ BT"
A Fir 14" dia., bears N.82°E., 13.5 ft. Scribed "C¼ BT"

BLM Dependent resurvey by Richard J. Dieckmann, Cadastral Surveyor, Group No. 2125, surveyed July 2006/Feb. 2007 - (DCSO records Vol. 55 Page(s) 21449)

The center ¼ sec. cor. of sec. 34, established by Wytcherley, in 2001, recorded in the Douglas County Surveyor's Office and is accepted as the cor.; monumented with an iron rod, 5/8" dia., firmly set, projecting 4" above the ground, with a plastic yellow cap mkd. WYTCHERLEY LS 2724, from which bearing trees mkd. by Wytcherley
A D.Fir, 16" dia., bears N.78¼°E., 13.5 ft. with scribe marks C¼ visible on partially healed blaze.
A D.Fir, 13" dia., bears S.46½°E., 13.6 ft., with no visible scribe marks on a partially healed blaze.
A D.Fir, 14" dia., bears S.43¼°W., 30.0 ft., with fragmentary scribe marks visible on partially healed blaze.
A D.Fir, 9" dia., bears N.20¼°W., 48.4 ft with fragmentary scribe marks visible on partially healed blaze.
At the corner point
Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, directly over the iron rod, with brass cap mkd.
T 32 S R 6 W
C ¼ S 34
2007
Deposit a magnet in a white plastic case at the base of the stainless steel post.
From this corner, a point established as the center ¼ sec. cor. by Lawrence, in 1955, bears N.13°41'W. 3.3 ft monumented with a bent iron pipe, ½" dia., firmly set, projecting 8" above the ground, and was not used for control in this survey