

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 27 and 34

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by George W. Hyde and Charles H. Gardner, Deputy Surveyors, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8650-51)

Set ¼ sec. post, from which
A W.Fir 12" dia., bears South, 33 lks. dist.
A Chinquapin 7" dia., bears N.31°E., 18 lks. dist.

Survey by H. W. Lawrence - Sept. 13, 1955 - C.S. File 42/327

Set 1" galv. Iron pipe 36" long, driven 28" into ground, from which
A R.Fir 24" dia. bears N.21°E., 41.0 ft. mkd ¼ S27 BT 1543
A Madrone 5½" dia. bears S.22°W. 29.0 ft mkd ¼ S34 BT 1543

Fd. OK, Max Hull, Jan. 1989, M 107-43
Fd. OK by R. Wytcherley, July 2001 - M137-18

BLM Dependent resurvey by Richard J. Dieckmann, Cadastral Surveyor, Group No. 2125, surveyed July 2006/Feb. 2007 - (DCSO records Vol. 55 Page(s) 21438-9)

The ¼ sec. cor of secs. 27 and 34, established by proportionate measurement, by Lawrence, in 1955, and utilized by various Oregon Professional Surveyors, there is no remaining evidence of the original cor.; therefore this position is accepted as the cor.; monumented with an iron pipe, 1¼" dia. firmly set, projecting 10" above the ground, from which bearing trees mkd. by Lawrence

A D.Fir, 32" dia., bears N.21¼°E., 42.1 ft., with visible bark scribes ¼S at breast height and BT near the base.
A madrone, 12" dia., bears S.23°W., 29.2 ft., with a healed blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, directly over the iron pipe, with brass cap mkd.

T32S R6W

¼ S 27
 S 34

2007

and a new bearing tree

A D.Fir, 24" dia., bears S.30¾°W., 32.8 ft., mkd. ¼ S34 BT
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center, unless otherwise described in the corner description

Deposit a magnet in a white plastic case at the base of the stainless steel post.