

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by W.H. Byars, under contract # 420 survey dated Sept. 16 1881 (DCSO records Vol. 20 Page(s) 8678)

Set a Yew post 3 ft. long, 3" sq., 24" in the ground, for 1/4 sec. cor., marked 1/4 S. on N. face, from which
A Yew 7" dia., bears South, 23 lks. mkd. 1/4 S BT.
A Fir 40" dia., bears N.18°W., 45 lks. dist., mkd. 1/4 S BT

BLM resurvey by Rollin D. Aanrud, Cadastral Surveyor, under Group #616, surveyed June 1966/March 1967 (DCSO records Vol. 34 Page(s) 13987-88)

The 1/4 sec. cor., monumented with a Yew post, 3 x 3 ins. sq., firmly set, protruding 18" above the ground, from which the original bearing trees:

The stump hole of a down Fir, 30" dia., bears N.18°W., 45 lks. dist., no marks visible on burned blaze on Fir.
A Yew stump 12" dia., bears South, 23 lks. dist., no marks visible.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked

| |
|--------------|
| T 32 S R 6 W |
| 1/4 S 15 |
| ----- |
| S 22 |

1966

from which new bearing trees

A Fir 7" dia., bears N.1°E., 67 lks. dist., mkd. 1/4 S15 BT
A Fir 8" dia., bears S.55°W., 27 lks. dist. mkd. 1/4 S22 BT

Reset Yew post alongside the iron post.

Cor. Fd. and used in BLM resurvey by Dixon and Hartley, under Group #1337, surveyed July/Sept. 1989 (DCSO records, Vol. 48 Page 18574)

Dan Saily - For: Juniper Properties LLC - Crew: Brett Ragon, Ignacio Roman & Trevor Clemo - 8/2024 - M184-12

Found - 1966 BLM brass cap and iron pipe marked T32S R6W 1/4 S15 S22 as per volume 34 pgs 13987-13988
Indeterminate size yew stump bears S.0 1/2 °E., 14.3' (rec South 15.18' {23 lks}). with a BLM tag, no visible face.
19" D.Fir bears S.53 1/4 °W., 17.9' (Rec S.55°W., 17.82' {27 lks}) with a blm tag and healed face.
20" D.Fir bears N.0 1/2 °W., 43.9' (Rec N.0 3/4 °W., 44.22' (67 lks)) with no tag and no visible face. We open a new face, scribe X 1/4 BT, and tag.

Continued next page

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 440400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 22

| | | | |
|-------|-------|-------------|-------|
| Alias | _____ | Description | _____ |
| Alias | _____ | Description | _____ |
| Alias | _____ | Description | _____ |
| Alias | _____ | Description | _____ |

New - 16" I.Cedar bears S.1¼°E., 23.0'. We scribe T32S R6W S22 ¼ BT and tag.

20" D.Fir bears N.51°W., 56.4'. We scribe T32S R6W S15 ¼ BT and tag.

Note - Could not locate stump hole at rec {N.18°W., 45 lks} Corner monument lies on a gentle east facing slope in mature timber, approximately 150' west of a dirt surface logging road. Top of monument is 0.5' above ground level.

We place a 5 1/2' tall steel galvanized U-post 1.0' East, on line.