

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 440640

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Section 3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by Orrin K. Frederick - For: Boise Cascade Timberlands of Oregon - Feb. 21, 1985 - C.S. File 63/11 and M 90-67

-----  
Set 5/8" x 30" iron rod with alum. cap mkd. LS 1987.  
BTs - 5" Fir bears N.59°45'W., 15.50 ft. mkd. C ¼ S3 LS 1987 BT.  
8" Cedar bears S.21°30'W., 41.04 ft. mkd. C ¼ S3 LS 1987 BT.

BLM survey by Mark Dixon and Henry Hartley, Cadastral Surveyors, under Group #1337, surveyed July/Sept. 1989 (DCSO records Vol. 48 Page(s) 18581-82)

-----  
The center ¼ sec. cor. established and recorded by Frederick in 1985, and is accepted as the corner; monumented with an iron rod 5/8" dia., firmly set, projecting 10" above ground, with alum. cap mkd. LS 1987 T32S R6W C¼ S3 1985, from which bearing trees mkd. by Frederick

A Cedar 6" dia., bears S.21½°W., 62 lks. dist., with scribe marks C¼ S3 LS 1987 BT visible on a partially healed blaze.

A Fir 5" dia., bears N.59 ¾°W., 23½ lks. dist., with scribe marks C¼ S3 LS 1987 BT visible on a partially healed blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. dia., 27 ins. in the ground, with brass cap marked  
T 32 S R 6 W  
C ¼ S 3  
1986

Deposit the iron rod inside and a white "DEEP-1" magnetic marker at base of the stainless steel post.