

PRIMARY CORNER DESCRIPTION No. ¼ Cor. Sec. 3 only; T33-6

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by George W. Hyde and Charles H. Gardner, Deputy Surveyors, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8636)

Set post, ¼ sec. cor., from which
A Red Fir 12" dia., bears S.55°W., 32 lks. dist.
A Red Fir 15" dia., bears S.40°E., 28 lks. dist.

Survey by Ronald A. Brandt - For: Robert Dollar Co. - Jan/May 1973 - C.S. File 55/294 and M 49-21

Set 1" x 36" I.Rod, 12" deep in Sether field, from which bears
1" x 36" I.Rod 4" high, N.46°55'34"E., 63.90 ft.
1" x 36" I.Rod 4" high, N.45°47'26"W., 49.59 ft.
(both set in a fence line)
1½" I.Pipe from C.S. File 42/327, N.89°31'26"W., 196.15 ft.
Fence line 38.50 ft. North of iron rod at corner.

Gerald Nygren - 11/23/94 - M121-31

Found - (Brandt cor.) 1" I.R., N.0°0'36"E., 2.25'.
(Brandt ref.) 1" I.R., N.45°33'29"E., 65.45'.
(Brandt ref.) 1" I.R., N.43°55'19"W., 51.18'.
(Brandt ref.) 1½" I.P., N.88°47'58"W., 196.18'.
Set - 5/8" I.R. 30" long 6" below ground w/cap mkd:
"NYGREN LS 1035"

Fd. OK by R. Wytcherley, July 2001 - M137-18 & CS65/38-3B

BLM Dependent resurvey by Richard J. Dieckmann, Cadastral Surveyor, Group No. 2125, surveyed July 2006/Feb. 2007 - (DCSO records Vol. 55 Page(s) 21447-8)

The standard ¼ sec. cor. of sec. 3, on the N. bdy. of T33S R6W, by Nygren, in 1994, bears S.88°46'43"E., 196.09 ft., there is no remaining evidence of the original cor.; this position was verified and is accepted as the cor.; monumented with an iron rod, 5/8" dia., firmly set, buried 8" below the ground, with a plastic yellow cap mkd. NYGREN LS 1035.
At the corner point
Set a stainless steel post, 28" long, 2½" dia., 43 " in the ground, top 15" below surface, directly over the iron rod, with brass cap mkd.

continued next page

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 443100

PRIMARY CORNER DESCRIPTION No. ¼ Cor. Sec. 3 only; T33-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

¼ S 3
T33S R6W
SC
2006

from which

A utility pole, No. E3993, bears S.30°E., 644.1 ft.

A utility pole, No. E4468, bears S.35¼°W., 604.1 ft.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From the standard ¼ sec. cor. of sec. 3, T. 33 S., R. 6 W., a point established as this same cor. by Brandt, in 1973, bears N.1°39'E., 2.3 ft., monumented with an iron rod, 1" diam., buried 12 ins. below the ground, and was not used for control in this survey.