

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by George W. Hyde and Charles H. Gardner, Deputy Surveyors, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8649)

Set ¼ sec. post, from which
 A B.Oak 15" dia., bears S.48°E., 61 lks. dist.
 A B.Oak 3" dia., bears N.49°W., 15 lks. dist.

George J. Wenderoth, Deputy County Surveyor - Sept. 1948 (no record source found, information from old Ren. #19, T32-6)

Find - 22" Oak with old blaze burnt out, use bearing N.58°W., 39.6 ft., set temp. stake.
 10" stump N.49°W., 9.9 ft., sit of old BT.
 Also measure North from top of ridge as per Govt. notes, 528 ft.
Drive 3/4" I. Pipe for corner.
Marked - 24" B.Oak S.39°08'E., 51.6 ft.
 10" W.Oak S.29°07'W., 36.0 ft.

Fd. OK, per Max Hull, Jan. 1989, M 107-43

James McIntosh - For: State of Oregon, Dept. of Forestry - May 2001 - M 138-28

Found - 3/4" IP, 1948 (in place)
 15" B.Oak (orig.) S.48°E., 61 lks., (now down & rotted no marks visible, roothole in place)
 3" B.Oak (orig.) N.49°W., 15 lks., (now a rotted stump with 4" Oak growing out of remains)
 24" B.Oak (1948) S.39°08'E., 51.6 ft. (now 24" in place, bottom of face open scribes visible on rotting face)
 10" W.Oak (1948) S.29°07'W., 36.0 ft. (now 14" in place, face closed)
New - WP (Orange carsonite marker CBM-250 labeled witness post) N.26°W., 3.9' to base.
 WP (Orange carsonite marker CBM-250 labeled witness post) N.65°E., 3.1' to base.