

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 26 and 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by George W. Hyde and Charles H. Gardner, Deputy Surveyors, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8649)

Set post, cor. to secs. 22, 23, 26 and 27, from which
A Laurel 5" dia., bears S.71°E., 47 lks. dist.
A Fir 6" dia., bears N.22°W., 18 lks. dist.
A Fir 20" dia., bears N.61°E., 60 lks. dist.
A Maple 5" dia., bears S.75°W., 44 lks. dist.

GLO survey by W.H. Byars, under contract # 420 survey dated Sept. 16 1881 (DCSO records Vol. 20 Page(s) 8669-70)

The post cor. to secs. 22, 23, 26 and 27, being destroyed, I re-establish same as per notes furnished. Bearing trees still standing, viz;
Set a Fir post, 4 ft. long, 4" sq., 24" in the ground, for the cor., marked T32S R6W S23 on NE.; S26 on SE.; S27 on SW.; and S22 on NW. faces with 2 notches on South and East edges, from which
A Laurel 5" dia., bears S.71°E., 47 lks. dist., mkd. T32S R6W S26 BT.
A Fir 6" dia., bears N.22°W., 18 lks. dist., mkd. T32S R6W S22 BT.
A Fir 20" dia., bears N.61°E., 60 lks. dist., mkd. T32S R6W S23 BT.
A Maple 5" dia., bears S.75°W., 44 lks. dist., mkd. T32S R6W S27 BT.

Survey by H.W. Lawrence - For: Martin - Nov. 1950/Mar. 1951 -C.S. File 40/306-1

The position of an old iron pipe was not found until the three adjoining ¼ corners were run. Inasmuch as this pipe was not on record at the County Surveyor's Office and also since it did not conform to my measurements or any sign of a bearing tree, it was disregarded in favor of the new position, now indicated by an iron pipe from which the center of the remains of a root structure of a large Fir bears N.61°E., 60 lks. dist., as given in the original survey notes. No sizable trees for BTs within 200 ft.

BLM Resurvey by Lynn Roseberry Cadastral Surveyor under Group #910 - Surveyed Aug/Sept. 1976 (DCSO records Vol. 41 Page(s) 16313)

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 26 and 27

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

The sec. cor., perpetuated and recorded by H.W. Lawrence in 1950-51, from original evidence no longer in existence, and further perpetuated and recorded by Lawrence in 1963, monumented with a galv. iron pipe, 3/4" dia., firmly set, projecting 6" above ground, with lead cap mkd. 22 23 26 27 1543.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked

T 32	S R 6 W
S 22	S 23
S 27	S 26
1976	

from which

A Fir 14" dia., bears N.5½°E., 84 lks. dist., mkd. T32S R6W S23 BT.

A Fir 16" dia., bears S.44°E., 120 lks. dist., mkd. T32S R6W S26 BT.

A Fir 13" dia., bears S.81 3/4°W., 106 lks. dist., mkd. T32S R6W S27 BT.

A Fir 11" dia., bears N.44 3/4°W., 70 lks. dist., mkd. T32S R6W S22 BT.

From this point, a corner reported by Lawrence in 1950-51, bears S.25¼°E., 0.335 chs. dist., monumented with an iron pipe 1¼" dia., firmly set, projecting 6" above ground.

Corner is located under a 3 strand power transmission line, bears N.57°E. and S.57°W.

Cor. Fd. OK, R. Brandt, 1977-78, C.S. File 58/125 and M 69-3 Fd. OK by J. McIntosh, May 2001 - M138-28

BLM dependent resurvey by Francis J. Simon, Cadastral Surveyor under Group #2160, surveyed March/April 2007 - (DCSO records Vol. 55 Page 21480)

 The cor. of secs. 22, 23, 26, and 27, monumented with an iron post, 2½ ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap (properly) mkd.

from which the remains of BTs mkd. by Roseberry and Aanrud

A sawed fir stump, 23" dia., bears N.5½°E., 55.4 ft., no marks visible on a portion of a healed blaze.

A sawed fir stump, 29" dia., bears S.44°E., 79.2 ft., with a healed blaze.

A fir, 19" dia., bears S.81¾°W., 70.0 ft., with a healed blaze.

A fir, 17" dia., bears N.44¾°W., 46.2 ft., with a healed blaze.

continued next page

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 26 and 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

and new bearing trees

A fir, 9" dia., bears S.24°E., 71.2 ft., mkd. T32S R6W S26 BT.

A cedar, 8" dia., bears N.8½°E., 62.8 ft., mkd. X at breast height and BT at the base.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center, unless otherwise described in the corner description

From this corner, a point established by person(s) unknown, reported by Lawrence in 1950-51, and Roseberry in 1976, bears S.23°56'00"E., 21.7 ft., monumented with an iron pipe, 1½" dia., firmly set, top 12" below the ground, bent to the west, apparently disturbed by power line road construction.

The monument set by Lawrence, an iron pipe, ¾" dia., firmly set, projecting 6" above the ground, with an aluminum cap set on a steel spring, mkd. S22 S23 S26 S27 1543, is alongside the iron post.

Fd as per record 5/2014 - By D. Edwards M168-10
Fd. BC 1/2020 - D Baker