

PRIMARY CORNER DESCRIPTION Sec. Cor. for 14, 15, 22 and 23

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W.H. Byars, under contract # 420 survey dated Sept. 16 1881 (DCSO records Vol. 20 Page(s) 8671)

Set a Laurel post, 4 ft. long, 4" sq., 24" in the ground, for the cor. to secs. 14, 15, 22 and 23, marked T32S R6W S14 on NE.; S23 on SE.; S22 on SW.; and S15 on NW. faces, with 3 notches on S. and 2 notches on East, edges, from which
A Laurel 6" dia., bears N.30°E., 22 lks. dist., mkd. T32S R6W S14 BT.
A Live Oak 6" dia., bears S.35°E., 16 lks. dist., mkd. T32S R6W S23 BT.
A Laurel 6" dia., bears S.70°W., 7 lks. dist., mkd. T32S R6W S22 BT.
A Live Oak 7" dia., bears N.50°W., 23 lks. dist., mkd. T32S R6W S15 BT.

Fd. Cor. by NW Oak, Lorne Van Swearingen, 1963, C.S. File 51/255

BLM resurvey by Rollin D. Aanrud, Cadastral Surveyor, under Group #616, surveyed June 1966/March 1967 (DCSO records Vol. 34 Page(s) 13983-84)

The sec. cor., determined at record bearing and distance from the only remaining original bearing tree
A Live Oak 14" dia., bears N.50°W., 23 lks. dist., with scribe mark 3 visible on weathered blaze.

At the corner point
Set an iron post, 28 ins. long, 2 1/2 ins. dia., 22 ins. in the ground, with brass cap marked
T 32 S R 6 W
S 15 S 14
S 22 S 23
1966

from which new bearing trees
A Fir 16" dia., bears N.9½°E., 69 lks. dist., mkd. T32S R6W S14 BT.
A Madrone 10" dia., bears S.72°E., 57 lks. dist., mkd. T32S R6W S23 BT.
A Madrone 8" dia., bears S.10°W., 43 lks. dist., mkd. T32S R6W S22 BT.
A Live Oak 12" dia., bears N.10°W., 22 lks. dist., mkd. T32S R6W S15 BT.

Cor. Fd., R. Brandt, 1977-78, C.S. File 58/125 and M 69-3

Fd. and used in BLM survey by Mark Dixon and Henry Hartley, under Group #1337, surveyed July/Sept. 1989 (DCSO records, Vol. 48 Page 18568)