

PRIMARY CORNER DESCRIPTION Sec. Cor. for 10, 11, 14 and 15

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W.H. Byars, under contract # 420 survey dated Sept. 16 1881 (DCSO records Vol. 20 Page(s) 8673)

Set Laurel post 4 ft. long, 4" sq., 24" in the ground, for cor. to secs. 10, 11, 14 and 15, marked T32S R6W S11 on NE.; S14 on SE.; S15 on SW.; and S10 on NW. faces, with 4 notches on S. and 2 notches on E. edges, from which

- A Laurel 6" dia., bears N.20°E., 28 lks. dist., mkd. T32S R6W S11 BT.
- A Laurel 10" dia., bears S.30°E., 81 lks. dist., mkd. T32S R6W S14 BT.
- A Laurel 8" dia., bears S.25°W., 13 lks. dist., mkd. T32S R6W S15 BT.
- A Laurel 7" dia., bears N.40°W., 8 lks. dist., mkd. T32S R6W S10 BT.

Survey by Lorne V. Swearingen - For: Robert Dollar Co. - 1963 - C.S. File 51/255 and M 25-48

Set 5/8" drill steel, set by double proportion. (see explanatory notes in CS File 51/255)

- New BTs -10" Fir S.39°41'W., 2.4 ft.
- 12" Madrone S.19°20'E., 19.5 ft.
- 22" Fir N.3°33'E., 41.6 ft.
- 6" Sugar Pine N.20°35'W., 46.4 ft.

BLM resurvey by Rollin D. Aanrud, Cadastral Surveyor, under Group #616, surveyed June 1966/March 1967 (DCSO records Vol. 34 Page(s) 13985)

The sec. cor., reestablished and recorded at proportionate distance by Lorne Searingen in 1963, monumented with a steel rod, 5/8" dia., firmly set, protruding 6" above ground; there is no remaining evidence of the original corner, from which bearing trees mkd. by Swearingen:

- A Fir 20" dia., bears N.5°E., 64 lks. dist., with partially healed blazed.
- A Madrone 16" dia., bears S.18°E., 32 lks. dist., with scribe marks S14 BT visible on open blaze.
- A Fir 14" dia., bears S.39°W., 4 lks. dist., with partially healed blaze.
- A Sugar Pine 8" dia., bears N.19°W., 69 lks. dist., with partially healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked

(Cont. Next Page)

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 10, 11, 14, 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

T 32 S R 6 W
S 10 S 11
S 15 S 14
1966

from which new bearing trees

A Fir 10" dia., bears N.16°E., 61 lks. dist., mkd. T32S R6W S11 BT.

A Sugar Pine 24" dia., bears S.58°W., 39 lks. dist., mkd. T32S R6W S15 BT.

Insert steel rod inside iron post.

Cor. falls on spur, slopes E.

Fd. OK, by Smith, April 27, 1983, M 94-19

BLM survey by Mark Dixon and Henry Hartley, Cadastral Surveyors, under Group #1337, surveyed July/Sept. 1989 (DCSO records Vol. 48 Page(s) 18569)

The sec.cor., monumented with an iron post, 2½" dia., firmly set, projecting 7" above ground, with 1966 brass cap, from which bearing trees mkd. by Swearingen in 1963

A Fir 25" dia., bears N.3¼°E., 63 lks. dist., with healed blaze. (Rec. N.5°E., 64 lks.)

A Madrone 18" dia., bears S.16°E., 31 lks. dist., with healed blaze. (Rec. S.18°E., 32 lks.)

A Fir 22" dia., bears S.39°W., 4 lks. dist., with healed blaze.

A Sugar Pine 14" dia., bears N.20¼°W., 69 lks. dist. with healed blaze. (Rec. N.19°W.)

and bearing trees mkd. by Aanrud

A Fir 15" dia., bears N.14¼°E., 61 lks. dist., with healed blaze. (Rec. N.16°E.)

A Sugar Pine 26" dia., bears S.58°W., 38 lks. dist., with healed blaze. (Rec. 39 lks.)

From this point, a point established by person(s) unknown, bears N.35°E., 0.70 chs. dist., monumented with a mound of stone, 3 ft. base, 1 ft. high.