

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 500640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 and 3

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, under contract # 420 survey dated Sept. 16 1881 (DCSO records Vol. 20 Page(s) 8676)

-----  
Set a Fir post 3 ft. long, 3" sq., 20" in the ground, for ¼ sec. cor., marked ¼ S. on W. face, from which  
A Fir 14" dia., bears East, 32 lks. mkd. ¼ S BT.  
A Fir 12" dia., bears N.80°W., 20 lks. mkd. ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, Joe Brady, crew - Oct. 1967 - C.S. File 54/53-23

-----  
Found - 14" now 31" D.Fir, East 21.8 ft., shows scar.  
12" now 28" D.Fir N.80°W., 13.2 ft. Tree had been opened, "B" and part of "T" visible.

Set Brass cap at cor. mkd: County Surveyors Office  
T 32 S R 6 W  
¼ S 3 S 2  
1967

Reblazed and rescribed:

28" D.Fir N.80°W., 13.2 ft. mkd. ¼ S3 CS BT.  
31" D.Fir East, 21.8 ft. mkd. ¼ S2 CS BT.

This corner lies on South side of a sharp ridge running East and approx. 230.0 ft. North of creek running NE.

Survey by Orrin K. Frederick, LS #1987 - For: Boise Cascade Timberlands of Oregon - Feb. 21, 1985 - C.S. File 63/11 and M 90-67

-----  
Found - 1967 DCSO brass cap monument loosely set and leaning easterly.

I RESET the monument, exposed 15", in a mound of stone at the corner point from which:

30" Fir bears N.80°W., 13.2 ft. lower blaze opened, "B" visible.

33" Fir bears East 21.8 ft. with healed blaze.

New BT - 9" Hemlock bears S.15°E., 52.14 ft. to center mkd. ¼ S2 LS 1987 BT.

Cor. Fd. and used in BLM survey by Dixon and Hartley under Group #1337, surveyed July/Sept. 1989 (DCSO records, Vol. 48 Page 18573)