

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 503100

PRIMARY CORNER DESCRIPTION No. Sec. cor. for 2 & 3 only

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

GLO survey by George W. Hyde and Charles H. Gardner, Deputy Surveyors, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8636)

Set post, cor. to secs. 2 and 3, T33S R6W, from which
A Laurel 4" dia., bears S.1°W., 40 lks. dist.
A Fir 24" dia., bears S.48°E., 92 lks. dist.

Survey by Ronald A. Brandt - For: Robert Dollar Co. - Jan/May 1973 - C.S. File 55/294 and M 49-21

Set 1" I. Rod 4" high, from which bears:
7.5" Madrone, South, 9.10 ft. mkd. S2 33-6 PS841 BT.
6.8" D.Fir S.87°02'W., 38.08 ft. mkd. S3 33-6 PS841 BT
Fenceline is 1.5 ft. North of iron rod.

Gerald Nygren - 11/23/94 - M 121 -31

Found - (Brandt cor.) 1" I.R., N.11°55'52"W., 2.62'
(Brandt BT.) 19" Douglas Fir, N.89°W., 38.6',
healed
blaze.
(Brandt BT.) 12" madrone, S.5°W., 6.6', visible
scribe
Set - 5/8" I.R. 30" long 2" above ground w/cap mkd: "NYGREN
LS 1035"
New BT - 9" Douglas fir, S.58°E., 10.5', scribed "T33S R6W
S2 BT".

FD. Ok by Mark Heimburger 11/2006 - M151-65