

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 540100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. Sec. 35 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by George W. Hyde and Charles H. Gardner, Deputy Surveyors, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8641)

-----  
Set ¼ sec. post, from which  
A Chinquapin 5" dia., bears N.15°E., 34 lks. dist.  
A Fir 18" dia., bears N.70°W., 22 lks. dist.

Not Fd by J.Powell, DCSO 10/1967 (added 3/28/2017) C.S. 54/53-35

Survey by Robert M. Thompson - For: Mohr and A. Wells - Nov. 15, 1971 - C.S. File 55/236 and M 44-38

-----  
Set 1½" I.Pipe and scribed "¼ S35 BT" on:  
14" D.Fir N.77°E., 54.0 ft.  
14" D.Fir S.11°W., 40.1 ft.

Mark Heimburger - For ODOT - 11/2006 - M151-65

-----  
Set - 5/8"x30" iron rebar with plastic cap mkd: "LANDMARK LS2287" from which  
1½" I. pipe per M44-38 bears N.35°28'17"W., 10.06'  
24" D.Fir bears N.71°E., 64.6'  
13" D.Fir bears N.10°W., 56.2'  
5/8" rebar w/plastic cap marked "LAND MARK LS2285" bears East 40.0'  
5/8" rebar w/plastic cap marked "LAND MARK LS2285" bears North 40.0'

BLM Dependent resurvey by Richard J. Dieckmann, Cadastral Surveyor, Group No. 2125, surveyed July 2006/Feb. 2007 - (DCSO records Vol. 55 Page(s) 21452-3)

-----  
The ¼ sec. cor. of sec. 35 only, on the S. bdy. of the Tp., reestablished by proportionate measurement, by Heimberger, in 2006, there is no remaining evidence of the original cor.; this position was verified and is accepted as the cor.; monumented with an iron rod 5/8" dia., firmly set, projecting 4" above the ground, with a plastic yellow cap mkd. PLS 2287 LANDMARK, from which BTs and accessories mkd. by Heimberger  
An iron rod 5/8" dia., firmly set, projecting 1" above the ground, bears North, 40.0 ft., with a plastic yellow cap mkd. PLS 2287 LANDMARK.  
A D.Fir, 22" dia., bears N.69¾°E., 64.5 ft., with scribe marks S¼ S35 BT visible on open blaze.  
An iron rod 5/8" dia., firmly set, projecting 1" above the ground, bears East, 40.0 ft., with a plastic yellow cap mkd. PLS 2287 LANDMARK. Continued next page

TOWNSHIP 33 RANGE 06 POINT IDENTIFIER # 537700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. Sec. 35 only, T32-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A D.Fir, 14" dia., bears N.35 $\frac{3}{4}$ °W., 57.2 ft., with scribe marks S $\frac{1}{4}$  S35 BT visible on open blaze.

At the corner point

Set a stainless steel post, 28" long, 2 $\frac{1}{2}$ " dia., directly over the iron rod, 24" in the ground, with brass cap mkd.

T32S R6W

$\frac{1}{4}$  S 35

T33S R6W

2006

The geographic position (NAD 1983(CORS96)) of the  $\frac{1}{4}$  section corner of section 35 only, on the south boundary of the township, as determined by a conventional tie to a temporary point, established utilizing NAVSTAR GPS static data and NGS Online Positioning User Service (OPUS) with NSRS CORS stations, "CAPE MENDOCINO 1", "KLAMATH FALLS 1", and "APPLETON", is as follows:

Latitude: 42°44'22.32"N. Longitude: 123°22'38.12"W.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this corner, a point established as the  $\frac{1}{4}$  sec. cor. of sec.35 by Thompson, in 1971, bears N.27°05'W., 9.5 ft. monumented with an iron pipe, 2" dia., firmly set, projecting 15" above the ground, and was not used for control in this survey, from which bearing trees mkd. by Thompson

A D.Fir, 20" dia., bears N.75 $\frac{1}{2}$ °E., 51.6 ft., with a healed upper and lower blazes.

A sawed D.Fir stump, 20" dia., bears S.10°W., 40.0 ft., with a partially healed blaze.

Also from the  $\frac{1}{4}$  sec. cor. of sec. 35 only, the standard  $\frac{1}{4}$  sec. cor. of sec. 2, on the N. bdy. of T33S R6W bears S.89°44'05"E., 198.65 ft.