

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent resurvey by Richard J. Dieckmann, Cadastral Surveyor, Group No. 2125, surveyed July 2006/Feb. 2007 - (DCSO records Vol. 55 Page(s) 21453-4)

-----  
N.0°02'24"W., on the N-S centerline of sec. 35 (from the S¼ Sec. 35) At 2637.13 ft:

Point for the center ¼ sec. cor. of sec. 35 at intersection with the E and W center line. This point falls in the riparian area for Cow Creek and no permanent monument was established.

At 3067.13 ft:

Point selected for a witness cor. to the center ¼ sec. cor. of sec. 35.

Set a stainless steel post, 28" long, 2½" dia., 34" in the ground, top 6" below surface, with brass cap mkd.

WC  
T 32 S R 6 W  
C  
C 1/4 | S 35



from which

A W.Oak, 23" dia., bears N.66½°W., 120.5 ft unmarked.

A utility pole, No. PPL E4029, bears N.36½°E., 77.1 ft.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From the ¼ sec. cor. secs. 35 & 36 N.89°57'42"W., on the E. and W center line of sec. 35 At 2909.50

Point selected for a Witness Point on the E and W center line of sec. 35.

Set a stainless steel post, 28" long, 2½" dia., 34" in the ground, with brass cap mkd.

WP  
C ——— C  
S 35  
2006

from which

An incense cedar, 15" dia. bears S.31¼°W. 75.0 ft unmarked

A maple, 23" dia., bears N.27¾°W., 105.2 ft., unmarked.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center, unless otherwise described in the corner description

Deposit a magnet in a white plastic case at the base of the stainless steel post.