

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 and 26

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W.H. Byars, under contract # 420 survey dated Sept. 16 1881 (DCSO records Vol. 20 Page(s) 8670)

Set a Maple post, 3 ft. long, 3" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S. on N. face, from which
A Laurel 14" dia., bears N.34°E., 48 lks. dist., mkd. ¼ S BT.
A Fir 16" dia., bears S.50°W., 57 lks. dist., mkd. ¼ S BT.

Survey by Ronald A. Brandt - For: Robert Dollar Co. - July 6, 1977 - C.S. File 58/149

Set by single proportion, a 1" x 36" Iron rod, 6" high in rock pile.
BTs - 8" Maple S.72°30'E., 9.51 ft. scribed ¼ S26 PS 841 BT
10" D.Fir N.74°W., 30.23 ft. scribed ¼ S23 PS 841 BT.
Evidence of the orig. 1881 survey not found. Corner area not logged but old burn left only burned stobs and snags which have since become totally rotted out.

Fd. by Brandt, 1977-78, C.S. File 58/125 and M 69-3

James McIntosh - For: State of Oregon, Dept. of Forestry - May 2001 - M 138-28

Found - 1" IR in mound of rock, 1977 (now out of ground)
8" Maple (1977) S.72°30'E., 9.51' (now 9" in place, scribes visible BT tag)
10" Fir (1977) N.74°W., 30.28' (now 15" in place, face closed)
New - WP (Orange carsonite marker CBM-250 labeled witness post) N.66°W., 3.7' to base.
WP (Orange carsonite marker CBM-250 labeled witness post) S.26°E., 2.9' to base.

BLM dependent resurvey by Randy Zanon, Cadastral Surveyor, under Group #1966, surveyed Sept/Nov 2001 - (DCSO records Vol. 54 Page(s) 20758-9)

The ¼ sec. cor. of secs. 23 & 26, established & recorded by Brandt in 1977, by proportionate measurement. There is no remaining evidence of the original corner; therefore this position is accepted as the best available evidence of the corner; monumented with an iron rod, 1" diam., firmly set, projecting 8" above the ground in a mound of stone, from which bearing trees mkd. by Brandt:

continued next page

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 540300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 and 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A maple, 10" dia., bears S.72½°E., 9.1 ft., with scribe marks S4 & other illegible scribe marks visible on partially healed blaze.

A fir, 14" dia., bears N.74°W., 31.0 ft., with a healed blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., directly over the iron rod, 6" in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 32 S R 6 W
¼ S 23
 S 26
 2001

Deposit a magnet in a white plastic case at the base of the stainless steel post.

FD. & used on BLM dependent resurvey by Francis J. Simon, Cadastral Surveyor under Group #2160, surveyed March/April 2007 - (DCSO records Vol. 55 Page(s) 21479)