

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 23

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Survey by Ronald A. Brandt, P.L. #841 - For: Robert Dollar Co. March 1, 1978 - C.S. File 58/125 and M 69-3

-----  
Set 1" x 36" I.R., 4" high from which bears  
12" Copco pole # E3292, S.48°30'E., 51.0 ft. mkd. C ¼ S23  
PS 841 RP.  
1" I.R., N.00°40'30"W., 528.00 ft.  
1" I.R., S.89°15'44"W., 495.00 ft.

BLM dependent resurvey by Francis J. Simon, Cadastral Surveyor under Group #2160, surveyed March/April 2007 - (DCSO records Vol. 55 Page(s) 21482-3)

-----  
The center ¼ sec. cor. of sec. 23, established by Brandt in 1978, and is accepted as the cor.; monumented with an iron rod, 1" dia., firmly set, projecting 2" above the ground, from which a power pole mkd. by Brandt:

A wood power pole, COPCO E3292, bears S.49¼°E., 50.6 ft., with scribe marks ¼ S23 & other illegible marks visible

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 28" in the ground, directly over the iron rod, in a collar of stone, with brass cap mkd.

T32S R6W  
C ¼ S 23  
2007

from which a new accessory

A wood power pole, with tag mkd. COPCO E3227, bears S.73°W., 230.7 ft.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

(NAD 1983 (CORS 96)

Latitude: 42°46'32.877" N.

Longitude: 123°22'38.526" W.