

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM survey by Mark Dixon and Henry Hartley, Cadastral Surveyors, under Group #1337, surveyed July/Sept. 1989 (DCSO records Vol. 48 Page(s) 18586)

Point for the center ¼ sec. cor. of sec. 14, at intersection with the E. and W. center line.

Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd: T 32 S R 6 W
C ¼ S 14
1986

from which

A Fir 14" dia., bears S.50°W., 63½ lks. dist., mkd. C ¼ S14 BT.

A Fir 12" dia., bears N.1¼°W., 56 lks. dist., mkd. C ¼ S14 BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

James McIntosh - For: Oregon State Dept. of Forestry - April 2000 - M134-72

Found - BLM pipe with brass cap 1986, in place.
14" Fir, 1986, S.50°W., 63½ lks., now 20" in place, face closed, bearing tree tag.
12" Fir, 1986, N.1¼°W., 56 lks., now 16" in place, face closed, bearing tree tag.

Rewitnessed -

14 Fir, N.78½°W., 43.1 ft to alum. nail in BT face scribed, C¼ S14 BT.

Orange carsonite marker CBM-250 labeled witness post, S.18°W., 2.4 ft. to base.