

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 11 and 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, under contract # 420 survey dated Sept. 16 1881 (DCSO records Vol. 20 Page(s) 8674)

-----

Set a Yew post, 3 ft. long, 3" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S. on N. face, from which

A Fir 30" dia., bears N.30°E., 36 lks. dist., mkd. ¼ S BT

A Fir 40" dia., bears S.30°W., 4 lks. dist., mkd. ¼ S BT.

(See C.S. File 51/255 and M 25-48 for information of search for this corner and setting a "hub". Survey by Lorne van Swearingen, 1963)

BLM resurvey by Rollin D. Aanrud, Cadastral Surveyor, under Group #616, surveyed June 1966/March 1967 (DCSO records Vol. 34 Page(s) 13985-86)

-----

The ¼ sec. cor., monumented with an iron pipe 1" dia., firmly set, protruding 12" above the ground, from which the original bearing trees:

The stump hole of a down Fir 28" dia., bears N.30°E., 36 lks. dist., no marks visible on the Fir.

A Fir snag 34" dia., bears S.30°W., 4 lks. dist., no marks visible on a burned blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap marked

T 32 S R 6 W

¼ S 11

S 14

1966

from which new bearing trees

A Fir 8" dia., bears N.5°W., 29 lks. dist., mkd. ¼ S11 BT.

A Fir 14" dia., bears S.54°W., 25 lks. dist., mkd. ¼ S14 BT.

Insert iron pipe inside iron post.

Cor. falls 125 lks. W. of Lawson Creek, 12 lks. wide, course South.

BLM resurvey by Rollin D. Aanrud, Cadastral Surveyor, under Group #1018, surveyed June/Aug. 1980 (DCSO records Vol. 44 Page(s) 16983)

-----

The ¼ sec. cor., monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 11 and 14

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

T 32 S R 6 W  
1/4 S 11  
S 14  
1966  
1980

from which the remains of the original bearing trees  
A root hole, bears N.30°E., 36 lks. dist., with a down Fir  
alongside, 28" dia., no marks visible.  
A Fir snag 34" dia., bears S.30°W., 4 lks. dist., with  
burned blaze, no marks visible.  
and bearing trees mkd. by Aanrud  
A Fir 22" dia., bears S.54°W., 25 lks. dist., with healed  
blaze.  
A Fir 9" dia., bears N.5°W., 29 lks. dist., with healed  
blaze.

Cor. Fd. and used in BLM survey by Dixon and Hartley, under  
Group #1337, surveyed July/Sept. 1989 (DCSO records, Vol. 48  
Page 18570)

James McIntosh - For: Oregon State Dept. of Forestry - April  
2000 - M134-72  
-----

Found - BLM pipe with brass cap 1966 & 1980, in place.  
30" Fir, 1882, N.30°E., 36 lks., now root hole in  
place, with down & very rotten log alongside.  
40" Fir, 1882, S.30°W., 4 lks., now 15" x 16' high  
rotted snag in place, no marks visible.  
14" Fir, 1966, S.54°W., 25 lks., now 27" in place,  
face closed, bearing tree tag.  
8" Fir, 1966, N.5°W., 29 lks., now 10" in place,  
face closed, bearing tree tag.

Rewitnessed -  
15" Fir S.58°E., 25.7 ft. to aluminum nail in BT  
face scribed ¼ S14 BT, bearing tree tag.  
Orange carsonite marker CBM-250 labeled witness  
post, N.61°W., 3.5' to base.