

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 540600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 and 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, under contract # 420 survey dated Sept. 16 1881 (DCSO records Vol. 20 Page(s) 8675)

Set a Fir post 3 ft. long, 3" sq., 24" in the ground, for 1/4 sec. cor., marked 1/4 S. on N. face, from which

A Laurel 20" dia., bears N.50°E., 24 lks. dist. mkd. 1/4 S BT.

A Fir 40" dia., bears S.35°W., 24 lks. dist., mkd. 1/4 S BT.

BLM resurvey by Rollin D. Aanrud, Cadastral Surveyor, under Group #1018, surveyed June/Aug. 1980 (DCSO records Vol. 44 Page(s) 16984)

Point for the 1/4 sec. cor. of secs. 2 and 11, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked T 32 S R 6 W

1/4 $\frac{S\ 2}{S\ 11}$
1980

from which

A Fir 6" dia., bears N.27 1/2°E., 59 lks. dist., mkd. 1/4 S2 BT.

A Fir 6" dia., bears S.24°E., 27 lks. dist., mkd. 1/4 S11 BT.