

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 600100

PRIMARY CORNER DESCRIPTION So. Sec. Cor. for 35 & 36 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - GLO survey by Geo. W. Hyde and Charles H. Gardner,
Deputy Surveyors, under Contract #54 dated Feb. 19, 1855
(DCSO records Vol. 20 Page(s) 8640)

Set post cor. to secs. 35 and 36, from which
A Fir 18" dia., bears N.40°W., 14 lks. dist.
A Fir 16" dia., bears N.61°E., 43 lks. dist.

George J. Wenderoth - Aug. 1955 - C.S. File 47/7

Found both O.B.T.s
Drive 1" iron pipe. Scribe two trees:
An 18" Fir N.60°33'E., 65.8 ft.
A 24" Fir N.33°50'W., 33.9 ft.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones,
Joe Brady, crew - Oct. 1967 - C.S. File 54/53-27

Found - 1" Iron pipe at corner.
18" D.Fir now snag, N.60½°E., 65.8 ft., scribe
visible "S BT"
24" now 25" D.Fir, N.34°W., 33.9 ft., shows good
scar.
New BT - 18" D.Fir N.84°E., 34.3 ft. mkd. T32S R6W S36 CS BT.
This corner lies on North slope approx. 20.0 ft. above old
skid road. Also 201.4 ft. West of C.C. of secs. 1 & 2, T33-6

John E. Hollingsworth, L.S. #691 - For: Oregon State Parks &
Recreation - June/Aug. 1988 - C.S. File 63/62 and M 107-16

Found - 1" Iron pipe projecting 6" above ground.
46" Fir bears N.56°W., (N.40°W) 9.0 ft. (9.2 ft.) to
illegible scribe marks in partially healed blaze.
(Orig.)
NE original BT falls in a skid road.
14" (18") Fir snag bears N.60°30'E., 65.8 ft. with
"36 BT" visible in partially healed double blaze.
22" Fir bears N.82°E., (N.84°E.) 38.0 ft. (34.3 ft.)
with healed blaze.
30" Fir bears N.36°W., N.33°50'W., 33.9 ft. with
healed blaze.
Set plastic cap in existing 1" iron pipe, mkd. "Oregon State
Parks".
Set orange carsonite post with decal mkd. "Property Boundary
State Park Land Behind This Sign", 2 ft. South.

Fd. 3/4" I.P., August 1990, M 110-48

continued next page

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 600100

PRIMARY CORNER DESCRIPTION So. Sec. cor. for 35 and 36 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

FD. Ok by Mark Heimburger 11/2006 - M151-65

BLM Dependent resurvey by Richard J. Dieckmann, Cadastral Surveyor, Group No. 2125, surveyed July 2006/Feb. 2007 - (DCSO records Vol. 55 Page(s) 21431-2)

The cor. of secs. 35 & 36 only, on the S. bdy. of the Tp., perpetuated by Wenderoth, in 1955, further perpetuated by the Douglas County Surveyor's Office in 1967, further perpetuated by Hollingsworth, in 1988, and utilized by various Oregon Professional Surveyors; monumented with an iron pipe, 1" dia. firmly set, projecting 10" above the ground, with a plastic yellow cap set inside the top, mkd. OREGON STATE PARKS from which an original bearing tree

A D.Fir, 54" dia., bears N.57 $\frac{3}{4}$ °W., 9.2 ft., with a healed blaze. (Record, N.40°W.)

and a bearing tree mkd. by Wenderoth

A D.Fir snag, 18" dia., bears N.59°E., 66.1 ft., with fragmentary scribe marks visible on a rotting blaze and BTs mkd. by the Douglas County Surveyor's Office

A D.Fir, 28" dia., bears N.82 $\frac{1}{4}$ °E., 37.9 ft., with a healed blaze.

A D.Fir, 37" dia., bears N.35 $\frac{1}{2}$ °W., 34.0 ft., with a healed blaze.

At the corner point

Set a stainless steel post, 28" long, 2 $\frac{1}{2}$ " dia., 24" in the ground, directly over the iron pipe, with brass cap mkd.

T32S R6W
S 35 | S 36
T33S R6W

S2

2006

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Ken Hoffine - For: Juniper Properties - Sept 2018 - M174-78

Found - 2006 BLM Brass cap 0.3 ft above ground

54" D.Fir bears N.57 $\frac{3}{4}$ °W., 9.1 ft (rec. N.57 $\frac{3}{4}$ °W., 9.2 ft) healed face and tag

28" D.Fir bears N.82 $\frac{1}{2}$ °E., 37.9 ft (rec. N.82 $\frac{1}{4}$ °E., 37.9 ft) healed face and tag

37" D.Fir bears N.36°W., 33.9 ft (rec. N.35 $\frac{1}{2}$ °W., 34.0 ft) healed face and tag corner lies on steep

North facing slope approx. 125 ft south of small draw. An orange carsonite post is approx. 2.0 feet south of corner.