TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 35 & 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by George W. Hyde and Charles H. Gardner, Deputy Surveyors, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8645)

Set ¼ sec. post, from which
A Laurel, 4" dia., bears S.60°W., 7 lks.
A Laurel, 4" dia., bears N.58°E., 3 lks.

BLM Dependent resurvey by Richard J. Dieckmann, Cadastral Surveyor, Group No. 2125, surveyed July 2006/Feb. 2007 - (DCSO records Vol. 55 Page(s) 21433-4)

Point for the ¼ sec. cor. of secs. 35 and 36 at proportionate distance, there is no remaining evidence of the original cor. Set a stainless steel post, 28" long, 2½" dia., 25" in the ground, with brass cap mkd. T32S R6W

¼
S 35|S 36
2006

from which
A ponderosa pine, 5" dia., bears S.89°E., 67.5 ft., mkd. X at breast height, BT at the base.
An incense cedar, 4" dia., bears S.74°W., 71.5 ft., mkd. X at breast height, BT at the base.
Deposit a magnet in a white plastic case at the base of the stainless steel post.

Fd. 2006 BLM BC & BTs by Ray Wytcherley, 3/2007 - M152-58

Ken Hoffine - For: Juniper Properties - Sept 2018 - M174-78

Found - 2006 BLM CAP
8" Pine bears S.89°E., 67.5 ft as per record healed face and BT tag
10" Cedar bears S.74°W., 71.55 ft (record S.74°W., 71.5 ft) healed face and BT tag corner lies in middle of cut slope of second bench in the cut slope for the North bound lanes of Interstate 5