

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25, 26, 35 and 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by George W. Hyde and Charles H. Gardner, Deputy Surveyors, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8645)

-----  
Set post cor. to secs. 25, 26, 35 and 36, from which  
A W.Oak 11" dia., bears N.20°30'W., 108 lks. dist.  
A W.Oak 24" dia., bears S.61°W., 509 lks. dist.  
An Ash 6" dia., bears S.21°E., 464 lks. dist.  
A Maple 14" dia., bears N.24°E., 70 lks. dist.  
(B.O. 6" N.22°E., 13.0 lks. by Briggs)

Survey by H. W. Lawrence - Oct. 2, 1954 - C.S. File 42/80

-----  
Place a stake 311 ft. North of section corner to secs. 25, 26, 35 and 36 for witness corner. Later, I drove a ½" iron rod at the stake, from which  
A B.Oak 29" dia., bears S.58°W., 20.5 ft. dist., mkd.  
WITNESS COR. BT 1543.  
Actual corner is in Cow Creek.

George J. Wenderoth - May 1955 - C.S. File 46/141

-----  
Set by Lawrence No. 1543, 331.0 ft. North of corner.  
Found - ½" iron rod.  
20" Ash S.59°50'W., 20.9 ft. mkd. 1543 BT.  
I drive ¾" Iron pipe over rod.  
Mark - 8" Ash N.33°40'W., 28.6 ft.  
Section corner falls in deep water of Cow Creek. Witness corner is on bank above gravel bar.

Not found, April 23, 1974, C.S. File 56/49-13

Survey by Ronald Brandt - For: Haggard, Webb, Williamson, etal Aug. 6, 1977 - C.S. File 58/125 and M 66-26

-----  
Set 1" x 36" iron rod, 6" high, from which bears  
11" Cottonwood N.10°30'E., 27.87 ft. scribed S25 PS841 BT  
12" Cottonwood S.59°W., 57.37 ft. scribed S26 PS841 BT.  
9.4" Cottonwood N.60°W., 56.46 ft. scribed S35 PS841 BT.  
Bent ¾" I.P., N.00°25'37"E., 330.20 ft. Witness corner.  
SE quadrant void of trees except very small willow and cottonwood.

Fd. 1" I.R., Aug. 1990, M 110-48  
Fd. 0k by R. Brown, 10/2005 - M148-69

continued next page

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25, 26, 35 and 36

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Mark Heimburger - For ODOT - 11/2006 - M151-65

-----  
Found - 1" iron rod & accessories per renewal.  
GRID N: 409467.694 GRID E: 4151302.346  
LATITUDE: 42°45'14.5207" LONGITUDE: -123°22'02.9260"  
CONVERGENCE: -1°57'42" GRID SCALE FACTOR: 0.99992063

BLM Dependent resurvey by Richard J. Dieckmann, Cadastral Surveyor, Group No. 2125, surveyed July 2006/Feb. 2007 - (DCSO records Vol. 55 Page(s) 21434-5)

-----  
The cor. of secs. 25, 26, 35, & 36, reestablished by proportionate measurement by Lawrence, in 1953, further perpetuated by Wenderoth, in 1955, and further perpetuated by Brandt, in 1977, and utilized by various Oregon Professional Surveyors, there is no remaining evidence of the original, therefore this position is accepted as the cor.; monumented with an iron rod, 1" dia., firmly set, projecting 3" above the ground, from which bearing trees mkd. by Brandt

A black cottonwood, 25" dia., bears S.59°W., 57.4 ft., with a healed blaze.

A black cottonwood, 19" dia., bears N.60°W., 56.5 ft., with a healed blaze.

and bearing trees mkd. by person(s) unknown

A black cottonwood, 22" dia., bears N.26½°E., 39.2 ft. no marks visible on a partially healed blaze.

A black cottonwood, 13" dia., bears S.32¼°E., 120.6 ft., with no marks visible on partially healed blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, directly over the iron rod, with brass cap mkd.

T32S R6W  
S 26 | S 25  
S 35 | S 36  
2006

Deposit a magnet in a white plastic case at the base of the stainless steel post. The cor. is located in a fence line, bears N. and S.

From this corner, a point established as a witness cor. by Lawrence and perpetuated by Wenderoth, bears N.0°08'00"W., 330.30 ft., this point now functions as a reference monument, monumented with an iron pipe, ¾" dia., firmly set, upper 12" bent to the North and flush with the ground, from which a bearing tree mkd. by Lawrence

A black oak, 39" dia., bears S.58°W., 20.5 ft., with a cut out blaze that has partially healed over.

Fd. 2006 BLM BC & BTs by Ray Wytcherley, 3/2007 - M152-58