

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 25 and 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by George W. Hyde and Charles H. Gardner, Deputy Surveyors, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8646)

Set ¼ sec. post on S. slope, from which
A B.Oak 15" dia., bears S.31°W., 20 lks. dist.
A B.Oak 4" dia., bears N.71°E., 8 lks. dist.

George J. Wenderoth - May 1955 - C.S. File 46/141

Found - Orig. B.Oak S.31°W., 13.2 ft. with scribe showing.
Set 1" Iron pipe. Marked:
22" B.Oak S.57°33'W., 39.3 ft.
26" Cedar N.23°39'W., 23.7 ft.

Feb. 1966
Set brass cap in place of iron pipe. See card in file.
(signed) George Wenderoth.

Douglas County Surveyors Office - R.B. Kimberling, Deputy, Mike Cline, crew - 8/17/1977 - C.S. File 59/38-17

Found - A 1" Iron pipe set 10" above ground with brass cap facing East mkd. "County Surveyors Office ¼ cor 26 25 T32S R6W LS 5"
A 15" now 19" B.Oak bears S.31°W., 13.2 ft. with partially healed rotted out single blaze.
A 22" B.Oak bears S.60°W., 40.2 ft. (Rec. S.57°33'W., 39.3 ft.) with partially healed rotted out single blaze.
A 26" dead Incense Cedar bears N.23°30'W., 23.7 ft. with partially healed double blaze and visible scribing "¼ CS BT"
New BT - A 9" D.Fir bears N.70½°E., 12.5 ft. double blazed and marked "¼ S25 T32S R6W CS BT".
From brass cap, fence runs West. N-S fence is 12 ft. West of brass cap.

Fd. OK, by Donald Bentz, Sept. 1986, M 102-39
Fd. Ok by Raymond Wytcherley Nov. 2005, M146-29
Fd. Ok by Raymond Wytcherley Dec. 2013, M167-36 A&B

continued next page

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 600240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 25 and 26

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

BLM dependent resurvey by Kevin G Mulder, Cadastral Surveyor, under Group No. 2925; Surveyed July/Oct. 2018 - (DCSO records Vol. 59 Page(s) 23763-4)

The ¼ sec. cor. of secs. 25 and 26, perpetuated by Wenderoth, in 1955 and 1966, further perpetuated by the Douglas Co. Surveyor's Office in 1977; monumented with an iron post, 1" dia., firmly set, projecting 8" above the ground, with brass cap oriented E. (Properly) mkd.

from which an original bearing tree

A B.Oak, 28" dia., bears S.31°W., 13.2 ft., with a healed blaze.

and a new bearing tree

A fir, 7" dia., bears N.61°E., 31.5 ft., mkd. ¼ S25 BT.
NAD 1983 (2011)

Latitude: 42°45'40.74" N. Longitude: 123°22'02.98" W.