

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13, 14, 23 and 24

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W.H. Byars, under contract # 420 survey dated Sept. 16 1881 (DCSO records Vol. 20 Page(s) 8663-64)

Set a Cedar post 4 ft. long, 4" sq., 22" in the ground for cor. to secs. 13, 14, 23 and 24, marked T32SR6W S13 on NE.; S24 on SE.; S23 on SW.; and S14 on NW. faces. Also 3 notches on S. and N. angles of same, from which
A Laurel 10" dia., bears N.35°E., 39 lks. dist. mkd. T32S R6W S13 BT.
A Laurel 18" dia., bears S.10°E., 16 lks. dist. mkd. T32S R6W S24 BT.
A Laurel 12" dia., bears S.65°W., 28 lks. dist. mkd. T32S R6W S23 BT.
A Laurel 18" dia., bears N.55°W., 23 lks. dist. mkd. T32S R6W S14 BT.

Ben B. Irving - Wit: N.E. Richardson; C.S. Henninger - Nov. 14, 1929 - C.S. File 37/12 (and "old" corner book, pg. 172)

Location identified from two original BTs, one dead and other partially so. Scribe marks chopped out and visible, as described in original notes. Reblazed and scribed:
O.B.T., N.55°W., 23 lks., Laurel, 24" dia., T32S R6W S14 CS BT.
Chinquapin N.55°W., 59 lks. T32S R6W S23.
Set Iron pipe for corner in mound of rocks.

George J. Wenderoth, Reg. Land Surveyor #5 - August 1945 (no record source found. Info. from old Ren. #7, T32-6)

Set 1" Iron pipe.
Chinquapin dead, N.55°W., 38.94 ft.
Laurel stump S.79°16'W., 15.18 ft.
No new trees available.

George J. Wenderoth, Deputy - For: R.L. VanDuine - May 23, 1963 - C.S. File 53/21

Found - 1" Iron pipe.
Old madrona BT, N.55°W., 15.2 ft., down.
Old BT, S.86°05'W., 39.4 ft.
Scribed -6" Madrona S.61°20'W., 19.6 ft.
10" Chinquapin N.52°07'W., 12.9 ft.
6" Madrona N.30°45'E., 13.7 ft.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13, 14, 23 and 24

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Cor. Fd. by R. Brandt, 1977-78, C.S. File 58/125 and M 69-3

BLM resurvey by Rollin D. Aanrud, Cadastral Surveyor, under Group #1018, surveyed June/Aug. 1980 (DCSO records Vol. 44 Page(s) 16975-76)

The sec. cor., perpetuated and recorded by Wenderoth in 1963, monumented with an iron pipe, 1" dia., firmly set, projecting 8" above ground, from which the remains of an original bearing tree:

A decayed Madrone stump, size indeterminate, bears S.10°E., 16 lks. dist., no marks visible.

and bearing trees mkd. by Wenderoth:

A Madrone 8" dia., bears N.30°E., 21 lks. dist., with scribe marks CS BT visible on partially healed blaze.

A Madrone 11" dia., bears S.60°W., 30½ lks. dist., with healed blaze.

A Chinquapin 12" dia., bears N.53°W., 20 lks. dist., with illegible scribe marks visible on partially healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 22 ins. in the ground, directly over iron pipe, and in a mound of stone, 2 ft. base, to top, with brass cap marked

T 32 S R 6 W
S 14 S 13
S 23 S 24
1980

from which a new bearing tree

A Madrone 8" dia., bears S.29½°E., 45 lks. dist., mkd. T32S R6W S24 BT.

B.L.M. Dependent resurvey by Francis Simon, Aug. - Sept. 1992 (DCSO records Vol. 51 Page(s) 19579-80)

Found - iron post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, in a collar of stone, 2 ft. base, to top, with brass cap.

Bearing trees mkd. by George J. Wenderoth

A madrone, 12 ins. diam., bears N. 30° E., 21 lks. dist., with illegible scribe marks visible on partially healed, double blaze.

An uprooted madrone, 11 ins. diam., bears S. 60° W., 30½ lks. dist., with healed blaze.

A chinquapin, 14 ins. diam., bears N. 53° W., 20 lks. dist., with illegible scribe marks visible on partially healed blaze.

(Cont. Next Page)

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13, 14, 23 and 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Bearing tree mkd. by Aanrud
A madrone, 9 ins. diam., bears S. 29½° E., 43½ lks. dist., with scribe marks T32S R6W S24 BT visible on partially healed blaze. (Record, 45 lks.)

New bearing tree
A chinquapin, 9 ins. diam., bears S. 32½° W., 67½ lks. dist., mkd. T32S R6W S23 BT.

Note - From this same point, a point erroneously established and recorded by George J. Wenderoth, Registered Land Surveyor No. 5, in 1963, County Survey record C.S. 53/21, as the ¼ sec. cor. of secs. 23 and 24, bears N. 2° 46' 30" W., 0.878 chs. dist., monumented with an iron pipe, 1 in. diam., firmly set, projecting 7 ins. above the ground.

Note - The corner is located 6 lks. south of woven wire fence, extends generally E. and W.