

PRIMARY CORNER DESCRIPTION Sec. Cor. from 11, 12, 13 and 14

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W.H. Byars, under contract # 420 survey dated Sept. 16 1881 (DCSO records Vol. 20 Page(s) 8665)

-
- Set a Yew post, 4 ft. long, 4" sq., 24" in the ground, for the cor. to secs. 11, 12, 13 and 14, mkd. T32SR6W S12 on NE.; S13 on SE.; S14 on SW.; and S11 on NW. faces with 4 notches on S. and 1 notch on E. edges, from which
- A Fir 40" dia., bears N.55°E., 50 lks. dist., mkd. T32S R6W S12 BT.
 - A Fir 48" dia., bears S.50°E., 76 lks. dist., mkd. T32S R6W S13 BT.
 - A Fir 20" dia., bears S.78°W., 32 lks. dist., mkd. T32S R6W S14 BT.
 - A Fir 40" dia., bears N.53°W., 40 lks. dist., mkd. T32S R6W S11 BT.

BLM resurvey by Rollin D. Aanrud, Cadastral Surveyor, under Group #1018, surveyed June/Aug. 1980 (DCSO records Vol. 44 Page(s) 16977)

-
- The sec. cor., determined at record bearing and distance from the remains of the original bearing trees:
- A root hole, bears N.55°E., 50 lks. dist., with a down Fir alongside, 40" dia., no marks visible.
 - A sawed Fir stump 44" dia., bears S.50°E., 76 lks. dist., no marks visible.
 - A root hole, bears S.78°W., 32 lks. dist.
 - A root hole, bears N.53°W., 40 lks. dist., with a down Fir alongside, 38" dia., no marks visible.

At the cor. point
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd. T 32 S R 6 W
S 11 S 12
S 14 S 13
1980

- from which new bearing trees:
- A Fir 15" dia., bears N.52°E., 32 lks. dist., mkd. T32S R6W S12 BT.
 - A Fir 11" dia., bears S.56 3/4°E., 52 lks. dist., mkd. T32S R6W S13 BT.
 - A Fir 8" dia., bears S.16°W., 72 lks. dist., mkd. T32S R6W S14 BT.
 - A Fir 7" dia., bears N.50 3/4°W., 28 lks. dist., mkd. T32S R6W S11 BT.