

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 600540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 11 and 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, under contract # 420 survey dated Sept. 16 1881 (DCSO records Vol. 20 Page(s) 8667)

-----  
Set a Yew post, 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor., mkd. ¼ S. on W. face, from which

A Dogwood, 9" dia., bears S.35°E., 16 lks. dist., mkd. ¼ S BT.

A Fir 10" dia., bears N.60°W., 11 lks. dist., mkd. ¼ S BT.

BLM resurvey by Rollin D. Aanrud, Cadastral Surveyor, under Group #1018, surveyed June/Aug. 1980 (DCSO records Vol. 44 Page(s) 16979)

-----  
Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 21 ins. in the ground, with brass cap marked

T 32 S R 6 W

1/4

S 11 | S 12

1980

from which

A Fir 11" dia., bears S.33½°E., 30 lks. dist., mkd. ¼ S12 BT.

A Fir 11" dia., bears N.46°W., 12½ lks. dist., mkd. ¼ S11 BT.

Found OK by K. Hoffine, Nov. 2002 - M141-34