

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1, 2, 11 and 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, under contract # 420 survey dated Sept. 16 1881 (DCSO records Vol. 20 Page(s) 8667)

Set a Cedar post 4 ft. long, 4" sq., 2 ft. in the ground for cor. to secs. 1, 2, 11 and 12, marked T32S R6W S1 on NE.; S12 on SE.; S11 on SW.; and S2 on NW. faces, with 5 notches on S. and 1 notch on E. edges, from which

- A Laurel 20" dia., bears N. marked T32S R6W S1 BT.
- A Fir 24" dia., bears S. marked T32S R6W S12 BT.
- A Laurel 20" dia., bears S. marked T32S R6W S11 BT.
- A Cedar 20" dia., bears N.72°W., 47 lks. dist., marked T32S R6W S2 BT.

BLM resurvey by Rollin D. Aanrud, Cadastral Surveyor, under Group #1018, surveyed June/Aug. 1980 (DCSO records Vol. 44 Page(s) 16979-80)

Point for the sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked

T 32 S R 6 W
S 2 S 1
S 11 S 12
1980

from which

- A Fir 10" dia., bears N.32°E., 29 lks. dist., mkd. T32S R6W S1 BT.
- A Fir 6" dia., bears S.40°E., 40½ lks. dist., mkd. T32S R6W S12 BT.
- A Fir 8" dia., bears S.16½°W., 16½ lks. dist., mkd. T32S R6W S11 BT.
- A Fir 6" dia., bears N.88¼°W., 46 lks. dist., mkd. T32S R6W S2 BT.