

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 600640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 1 and 2

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, under contract # 420 survey dated Sept. 16 1881 (DCSO records Vol. 20 Page(s) 8669)

-----  
Set a Fir post 3 ft. long, 3" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S. on W. face, from which  
A Fir 30" dia., bears N.30°E., 5 lks. dist., mkd. ¼ S BT.  
A Fir 16" dia., bears West 11 lks. mkd. ¼ S BT.

Not Fd. by John Powell, DCSO 10/1967 (added 3/28/2017) C.S. File 54/53-22 - Logged early 1900's & burnt.

BLM resurvey by Rollin D. Aanrud, Cadastral Surveyor, under Group #1018, surveyed June/Aug. 1980 (DCSO records Vol. 44 Page(s) 16982)

-----  
Point for the ¼ sec.cor., at proportionate distance; there is no remaining evidence of the original corner.  
Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked  
T 32 S R 6 W  
1/4  
S 2 | S 1  
1980

from which  
A Fir 15" dia., bears S.63°E., 26 lks. dist., mkd. ¼ S1 BT  
A Fir 10" dia., bears N.21½°W., 19 lks. dist. mkd. ¼ S2 BT