

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 603100

PRIMARY CORNER DESCRIPTION Stand. Cor. for Secs. 1 & 2 only, T33-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - GLO survey by Geo. W. Hyde and Charles H. Gardner, Deputy Surveyors, under Contract #54 dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8635)

Set Post, from which

A Fir 15" dia., bears S.75°E., 33 lks. dist.

A Fir 10" dia., bears S.33°W., 20 lks. dist.

George Wenderoth - August 1955 - C.S. File 47/7

Drive a 1" Iron pipe and scribe two trees:

14" Maple S.10°50'W., 57.0 ft.

14" Fir N.83°20'E., 78.8 ft.

Survey by John E. Hollingsworth, L.S. #691 - For: Oregon State Parks & Recreation - Jun/Aug. 1988 - C.S. File 63/62 and M 107-16

Found - 1" I.P. projecting 6" above ground.

30" (15") Fir stump bears S.75°E., 21.8 ft. with a badly decayed face and backcast, no marks visible. (Original)

A 10" stump bears S.33°W., 13.2 ft. to face with illegible partial scribe marks. (Orig.)

16" Fir snag bears N.83°20'E., 78.8 ft. mkd. "S 1-BTS 8 BT".

A 16" Maple bears S.10°50'W. 57.0 ft w/healed blaze
Set plastic cap in 1" existing iron pipe mkd. Oregon State parks.

New BT - A 11" Fir bears S.83°E. 21.6 ft mkd "T33S R6W S1 BT"

Set orange carsonite post with decal marked "Property Boundary State Park Land Behind this Sign", 2 ft. SW.

Fd. 3/4" I.P., Aug. 1990, M 110-48

BLM Dependent resurvey by Richard J. Dieckmann, Cadastral Surveyor, Group No. 2125, surveyed July 2006/Feb. 2007 - (DCSO records Vol. 55 Page(s) 21432-3)

The standard cor. of secs. 1 & 2 on the N. bdy. of T33S R6W bears N.89°35'03"E., 200.23 ft., perpetuated by Wenderoth, in 1955, further perpetuated by Hollingsworth, in 1988, utilized by various Oregon Professional Surveyors, monumented with an iron pipe, 1" dia., firmly set, projecting 14" above the ground, with a plastic yellow cap set inside the top, mkd. OREGON STATE PARKS, from which the remains of the original bearing trees

continued next page

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 603100

PRIMARY CORNER DESCRIPTION Stand Cor. for Secs 1 & 2 only; T33-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A decayed D.Fir stump, of indeterminate size, bears S.75°E., 21.8 ft., no marks visible.
A decayed D.Fir stump, of indeterminate size, bears S.33°W., 13.2 ft., no marks visible.
and bearing trees mkd. by Wenderoth
A broken off D.Fir snag, 15" dia. bears N.83½°E., 77.0 ft. with fragmentary scribe marks visible on rotting blaze
A maple, 17" dia. bears S.10¼°W. 56.1 ft with healed blaze and a bearing tree mkd. by Hollingsworth
A D.Fir, 15" dia. bears S.78¾°E. 22.2 ft with healed blaze
At the corner point
Set a stainless steel post, 28" long, 2½" dia., 26" in the ground, directly over the iron pipe, with brass cap mkd.

S 2 | S 1
T33S R6W
SC
2006

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Ken Hoffine - For: Juniper Properties - Sept 2018 - M174-78

Found - 2006 BLM brass cap
17" D.Fir bears S.78¾°E., 21.7 ft (rec. S78¾°E 22.2 ft) healed face and BT tag
19" Maple bears S.10¼°W., 56.1 ft record bearing and distance root wad prevented us from measuring to Maple.
Corner lies on South edge of old skid road. A carsonite post bears Southwest 0.7 feet.