

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 13

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Lloyd Smith - For: Oregon Department of Forestry - March 1997  
- M 124-46

-----  
Set - O.S.D.F. 1½"x30" alum. pipe with 3 3/4" alum. cap & magnetic insert.  
27" P.Pine N.18°W., 48.7' to aluminum nail in BT face scribed (T32SR6W C ¼ S13) Bearing Tree tag.  
15" Fir, N.15°E., 11.3' to aluminum nail in BT face scribed (T32SR6W C ¼ S13) Bearing Tree tag.  
Orange Carsonite marker CBM-250 labeled witness post, bears S.39°E., 3.4' to base.  
Orange Carsonite marker CBM-250 labeled witness post, bears S.35°W., 3.3' to base.  
Orange Carsonite marker CBM-250 labeled witness post, bears N.39°W., 4.4' to base.  
4"x4"x4" white painted cedar post bears, N.82°W., 4.4'.  
Fence North 9.4', Course East & West.

BLM dependent resurvey by Kevin G Mulder, Cadastral Surveyor, under Group No. 2925; Surveyed July/Oct. 2018 - (DCSO records Vol. 59 Page(s) 23766)

-----  
The center ¼ sec. cor. of sec. 13, established by Smith, in 1997, and is accepted as the cor.; monumented with an aluminum post, 1½" dia., firmly set, projecting 6" above the ground, with aluminum cap mkd.

STATE OF OREGON  
DEPARTMENT OF FORESTRY  
T32S R6W  
C¼ S 13  
1997  
LS 1101

from which bearing trees mkd. by Smith  
A fir, 18" dia., bears N.12°E., 11.8 ft., with a healed blaze.  
A ponderosa pine, 30" dia., bears N.22¼°W., 50.8 ft., with no marks visible on partially healed blaze.