

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 700100

PRIMARY CORNER DESCRIPTION SE Cor. Sec. 36 (SW cor. S31, T32-5)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Butler Ives and George W. Hyde, under Contract #39, dated January 4, 1854 - (DCSO records Vol. 20 Page(s) 8551)

Set post cor. of tps. 32 and 33 S. Rs. 5 and 6 W. on N. slope of hill, from which
A Laurel 10" dia., bears N.88°W., 30 lks.
A Laurel 5" dia., bears N.38°E., 30 lks.
A Laurel 10" dia., bears S.38°E., 54 lks.
A Fir 24" dia., bears S.37°W., 69 lks.

Douglas County Surveyors Office, James Byron, Deputy - For: C & D Lumber Co. - Aug. 19, 1958 - C.S. File 49/112 and M 12-51

Found - 1¼" Axle at corner and large Fir stump, S.37°W., 45.5 ft.
New BTs -8" R.Fir N.3°30'W., 15.4 ft. (scribed by R.E. 3024)
40" R.Fir N.7°E., 42.0 ft.

Revisited this corner March 19, 1968 and find as recorded in 1958. Also find call to creek to West checks record. We also find now 23" Laurel, center rotted checks record for NE BT. and stump hole that checks record for NW BT. We open "new" NW R.Fir BT and find scrbied by R.E. 3024.

Fd. OK, August 1990, M 110-48

BLM dependent resurvey by Terrence O. Nickerson, Cadastral Surveyor under Group #1474 survey Feb. 1989/June 1992 - (DCSO records Vol. 53 Pg(s) 20357-8)

The closing corner of T32S R5 & R6, perpetuated by person(s) unknown, subsequently perpetuated & recorded by the Douglas Co. Surveyor's Office in 1958, monumented with an iron rod, 1¼" dia., firmly set, projecting 14" above the ground, from which an OBT:
A Madrone, 24" dia., bears N.15°E., 12 lks., no marks visible.
and the remains of a BT recorded by the DCSO
A decayed Fir stump, size indeterminate, bears S.37°W., 69 lks., no marks visible.
and BTs mkd. by the DCSO
A Fir, 42" dia., bears N.7°E., 64 lks., with healed double blaze.
A Fir, 14" dia., bears N.5°W., 23 lks., with healed double blaze.
continued next page

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 700100

PRIMARY CORNER DESCRIPTION SE Cor. Sec. 36 (SW cor. S31, T32-5)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

At the corner point
Set an iron post, 28" long, 2½" dia., 22" in the ground, with
brass cap marked:

T32S
R 6 W R 5 W
CC
S 36 | S 31
S 1
T33S R6W
1989

Deposit white "DEEP-1" magnetic marker at base and iron rod
alongside the stainless steel post.

Ken Hoffine - For: Juniper Properties - Sept 2018 - M174-78

Found - A 1989 BLM brass cap
24" Madrone bears N.12°E., 8.0 ft (record N.15°E.,
7.92 ft) no visible marks and BT tag
48" D.Fir bears N.4½°E., 41.6 ft (record N.7°E.,
42.24 ft) healed face and BT tag
23" D.Fir bears N.6¼°W., 15.1 ft (record N.5°W.,
15.18 ft) healed face and BT tag corner lies on
spur ridge that runs northerly from corner.