

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 24; & 19 of T32-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - George W. Hyde and Wells Lake, under Contract #54 dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8554)

Set qr. sec. post, from which
A W.Oak 10" dia., bears S.19°W., 298 lks.
A B.Oak 22" dia., bears N.38½°E., 318 lks.

G.J. Wenderoth, Deputy Co. Surveyor - Wit: F.Loso and Joe Grey - March 3, 1950 - C.S. File 45/45 and M 27-12

Found - 24" W.Oak S.19°W., 196.7 ft. Center of tree all rotten.
40" B.Oak N.38°30'E., 209.8 ft. tree uprooted.
Drive 1" I.Pipe for corner.
Scribe - 12" W.Oak S.78°20'W., 59.2 ft.
14" W.Oak N.12°45'E., 194.0 ft.

Corner located in fence corner, DCSO, John Powell, August 17, 1967, C.S. File 53/52-10

B.L.M. Dependent resurvey by Francis Simon, Aug. - Sept. 1992 (DCSO records Vol. 51 Page(s) 19575)

Beginning at the 1/4 sec. cor. of secs. 19 & 24, on the E. bdy. of the Tp., perpetuated & recorded by Wenderoth, in 1950, from evidence no longer in existence, monumented with an iron pipe, 1" diam., firmly set 2" below the surface of the ground, from which bearing trees mkd. by Wenderoth:

A W.Oak, 23" diam., bears N.12½°E., 293½ lks. with healed blaze.

A W.Oak, 12" dia., bears S.78¼°W. 90 lks with healed blaze
At the corner point

Set a stainless steel post, 28" long, 2½" diam., directly over the iron pipe, 24" in the ground, with brass cap mkd.

T32S
R6W R5W
1/4
S 24 | S 19
1992

Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.

The corner is located 3 lks. N. of the corner of a barbed wire fence, 4 strands, extends E. and S.

Fd. Ok by Ray Wytcherley - 3/2002 - M139-65

FD. 3/4" IP & BTs per M27-12, 3/2008 M146-77 by R. Wytcherly

continued next page

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 700340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 24; & 19 of T32-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent resurvey by Arthur R. Rambo, & Francis Simon
Cadastral Surveyors under Group No. 2143, surveyed May
2006/Feb. 2007 - (DCSO records, Vol. 55 Page(s) 21704-5)

The ¼ sec. cor. of secs. 19 and 24, on the W. bdy. of the
Tp., monumented with an iron post, 2½" dia., firmly set,
projecting 2" above the ground, with brass cap (properly) mkd
from which bearing trees mkd. by Wenderoth in 1950, reported
by Simon in 1992

An oak, 24" dia., bears N.12½°E., 193.7 ft., with a healed
blaze.

An oak, 12" dia., bears S.78¼°W., 59.4 ft., with a healed
blaze.

The corner is located 2 ft. N. of the corner of a barbed wire
fence, 4 strands, extends E. and S.