

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 700440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 18 T32-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - George W. Hyde and Wells Lake, under Contract #54 dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8554)

Set ¼ sec. post. (ascend SE. slope) Va. 19°10'E.) from which:
A Cedar, 8" dia., bears S.47½°W., 22 lks.
A Fir, 6" dia., bears N.68°E., 42 lks.

Lloyd Smith - For: Oregon Department of Forestry - March 1997 - M 124-46

Set - O.S.D.F. 1½"x36" alum. pipe with 3 ¾" alum. cap & magnetic insert, in ground.
21" Fir, N.82°W., 91.3' to aluminum nail in BT face scribed (T32SR6W S13) Bearing Tree tag.
16" Fir, N.12°W., 79.5' to aluminum nail in BT face scribed (T32SR6W S13) Bearing Tree tag.
Orange Carsonite marker CBM-250 labeled witness post, bears S.88°E., 2.5' to base.
Orange Carsonite marker CBM-250 labeled witness post, bears S.11°E., 2.9'to base.
4"x4"x4" white painted cedar post, bears N.41°E., 2.0'.
Corner falls on NW Side of power & gas line right of way, course N.40°E.

BLM Dependent resurvey by Arthur R. Rambo, & Francis Simon Cadastral Surveyors under Group No. 2143, surveyed May 2006/Feb. 2007 - (DCSO records, Vol. 55 Page(s) 21671-2)

The ¼ sec. cor. of secs. 13 and 18, on the W. bdy. of the Tp., reestablished by proportionate measurement, by Lloyd D. Smith, in 1997. There is no remaining evidence of the original cor., therefore this position is accepted as the cor.; monumented with an iron post, 1½" dia., firmly set, projecting 7" above the ground, with an aluminum cap, (properly) mkd.
from which bearing trees mkd. by Smith
A fir, 32" dia., bears N.84¼°W., 91.6 ft., with no marks visible on partially healed blaze.
A fir, 19" dia., bears N.14¾°W., 79.1 ft., with no marks visible on partially healed blaze.
Cor. falls in the NW. side of power and gas line right of way, course N.40°E.

continued next page

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 700440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 18 T32-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM dependent resurvey by Kevin G Mulder, Cadastral Surveyor,
under Group No. 2925; Surveyed July/Oct. 2018 - (DCSO records
Vol. 59 Page(s) 23767)

The ¼ sec. cor. of secs. 13 & 18, on the E. bdy. of the Tp.,
reported by Rambo and Simon in 2006-07, monumented with an
aluminum post, (Record, iron post) 1½" dia., firmly set,
projecting 8" above the ground, with aluminum cap (properly)
mkd.

from which bearing trees reported by Rambo and Simon

A fir, 24" dia., bears N.84¼°W., 92.1 ft., with a healed
blaze. (Record, 91.6 ft.)

A fir, 21" dia., bears N.14¾°W., 79.1 ft., with a healed
blaze.

and a new bearing tree

A cedar, 11" dia., bears S.58¾°E., 131.4 ft., mkd. ¼ S18
BT.