

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - George W. Hyde and Wells Lake, under Contract #54 dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8555-56)

Set post, cor. to secs. 1, 6, 7 and 12 on E. slope of mountain, from which

- A Cedar 7" dia., bears S.24°W., 56 lks.
- A Cedar 8" dia., bears N.24°E., 59 lks.
- A Cedar 8" dia., bears N.36°W., 39 lks.
- A Fir 5" dia., bears S.63½°E., 34 lks.

GLO survey by Oscar F. Thiel, Deputy Surveyor, under Contract #729, dated Dec. 24, 1900 (DCSO records Vol. 20 Page(s) 8609)

(July 26, 1902)
The Sec. cor., which has disappeared. I replace it by setting a Cedar post, 3 ft. long, 4" sq., 24" in the ground, marked T32S S6 on NE.; R5W S7 on SE.; S12 on SW.; and R6W S1 on NW. faces, with 1 notch on N. and 5 notches on S. edges, from which

- A Cedar 10" dia., bears N.24°E., 59 lks. mkd. T32S R5W S6 BT. (Old BT)
- A Fir 40" dia., bears S.40°E., 27 lks. mkd. T32S R5W S7 BT. (New BT)
- A Cedar 10" dia., bears S.11°W., 59 lks. mkd. T32S R6W S12 BT. (New BT)
- A Cedar 10" dia., bears N.36°W., 39 lks. mkd. T32S R6W S1 BT. (Old BT)

Survey by Oregon State Board of Forestry, Louis W. Amort - D. Bagger, transitman - April 29, 1960 - C.S. File 42/341

Orig. Cedar post missing, from which a:
8" Cedar bears N.24°E., 59 lks., now 8" rotten uproot, faced, no scribes.
5" Cedar bears S.63°E., 34 lks., missing.
7" Cedar bears S.24°W., 56 lks., now 12" uproot, scribed T32S R6W S12 visible.
8" Cedar bears N.36°W., 39 lks., now 12" uproot, face burnt, original axe work remaining on lower edge of face.
48" line tree, 8.39 chs. North, found 48" uproot in place.
Resurvey, July 1902, Cedar post missing from which a:
40" Fir bears S.40°E., 27 lks., now 42", portion of face visible in bark.
Set 1½" x 36" galv. I.P. with bronze cap mkd: Ore.St.Bd.of Forestry T32S R5W R6W S1 S6 S7 S12 1960 RE2311, 30" in ground.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec Cor for 1 & 12; 6 & 7, T32-5

Alias	Description
Alias	Description
Alias	Description
Alias	Description

New BTs -9" Cedar bears N.26½°E., 82.6 ft. scribed T32S R5W S6 BT.
23" Cedar bears N.67°W., 27.4 ft. scribed T32S R6W S1 BT RE2311.
26" Cedar bears S.34°W., 47.1 ft. scribed T32S R6W S12 BT.
42" Fir bears S.28°E., 12.0 ft. scribed T32S 5W S7 BT.
Oregon St. Bd. of Forestry metal location poster on 42" Fir BT. Set 4"x4"x60" white painted Cedar post 2 ft. NE of pipe.

BLM resurvey by Rollin D. Aanrud, Cadastral Surveyor, under Group #1018, surveyed June/Aug. 1980 (DCSO records Vol. 44 Page(s) 16980-81)

The Sec. cor. perpetuated and recorded by Louis Amort, in 1960, monumented with an iron post, 1½" dia., firmly set, projecting 6" above ground with properly mkd. brass cap, from which the remains of the original bearing trees
A root hole bears N.24°E., 59 lks. dist. with a down and decayed Cedar alongside, size indeterminate, no marks visible.
A root hole bears S.24°W., 56 lks. dist. with a down Cedar alongside, 8" dia., no marks visible.
A root hole bears N.36°W., 39 lks. dist., with a down and decayed Cedar alongside, size indeterminate, with illegible scribe marks visible on overgrowth.
and the remains of bearing trees by Amort
A root hole bears N.16½°E., 100 lks. dist., with a down Cedar alongside 14" dia., with illegible scribe marks visible on partially healed blaze.
A Fir 42" dia., bears S.28°E., 18 lks. dist., with scribe marks T32S R5W S7 BT visible on partially healed blaze.
A Cedar 32" dia., bears S.34°W., 71 lks. dist., with illegible scribe marks visible on partially healed blaze.
A Cedar 30" dia., bears N.67°W., 41½ lks. dist., with scribe marks T32S R6W S1 BT RE 2311 visible on partially healed blaze.
and a new bearing tree
A Fir 6" dia., bears N.50°E., 9½ lks. dist., mkd. T32S R6W S6 BT.

Found OK by K. Hoffine, Nov. 2002 - M141-34

continued next page

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 700600

PRIMARY CORNER DESCRIPTION Sec Cor for 1 & 12; 6 & 7, T32-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

The cor. of secs. 1, 6, 7, and 12, reported by Aanrud in 1980, monumented with an iron post, 1½" dia., firmly set, projecting 5" above the ground, with brass cap (properly) mkd from which the remains of bearing trees reported by Aanrud

A fir, 15" dia., bears N.54°E., 6.3 ft., with a healed blaze. (Record, N.50°E.)

A broken off and rotted fir snag, size indeterminate, bears S.28°E., 11.9 ft., with scribe marks T32S R5W S7 BT visible on open blaze.

A cedar, 42" dia., bears S.32°W., 46.0 ft., with a healed blaze. (Record, S.34°W., 46.9 ft.)

A cedar, 32" dia., bears N.68¼°W., 27.4 ft., with a healed blaze. (Record, N.67°W.)

and a new bearing tree

A fir, 16" dia., bears S.11¼°E., 19.8 ft., mkd. T32S R5W S7 BT.

NAD 1983 (2011)

Latitude: 42°48'43.83" N. Longitude: 123°20'52.51" W.