

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 700640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 1; & 6 of T32-5

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Original - George W. Hyde and Wells Lake, under Contract #54 dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8556)

-----  
Set qr. sec. post on N. slope, from which  
A Chinquapin 8" dia., bears N.52°E., 3 lks.  
A Fir 8" dia., bears West 20 lks.

Survey by George Wenderoth - For: C & D Lumber Co. - April 11, 1959 - C.S. File 49/92

-----  
Found - 22" Fir, West 13.2 ft.  
Scribed -24" Fir S.12°18'E., 18.2 ft.  
14" Fir N.42°40'E., 20.1 ft.  
Set 3/4" Iron pipe for corner.

BLM dependent resurvey by Kevin G Mulder, Cadastral Surveyor, under Group No. 2925; Surveyed July/Oct. 2018 - (DCSO records Vol. 59 Page(s) 23761)

-----  
The ¼ sec. cor. of secs. 1 and 6, perpetuated by Wenderoth in 1959, determined at record bearing and distance from an original bearing tree

A fir, 30" dia., bears West, 13.2 ft., with a healed blaze.

and a bearing tree mkd. by Wenderoth

A fir, 27" dia., bears N.42½°E., 20.1 ft., with a healed blaze.

Set a stainless steel post, 28". long, 2½" dia., 24" in the ground, with brass cap mkd.

T32S  
¼  
R6W R5W  
S 1|S 6  
2018

The iron pipe monument established by Wenderoth in 1959 was found lying loose near record position. Deposit the iron pipe inside of the stainless steel post.