

PRIMARY CORNER DESCRIPTION SW Cor. Sec. 31 (Tp. Cor.)

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 20 Page(s) 8705-06 and 8706)

The standard corner to Tps. 32 S Ranges 7 and 8 West, which is a post, 4½ ft. long, 4" sq., marked S C T32S on N.; R7W S31 on E.; and R8W S36 on W. faces, with six notches on NE. and W. faces, from which:

A Pine 28" dia., bears N.57°E., 50 lks. dist.
 A Pine 36" dia., bears N.20°W., 80 lks. dist.
 A Fir 34" dia., bears S.20°E., 62 lks. dist.

Fd. and described in GLO survey by Richmond S. Dickerson, Deputy Surveyor, under Contract #474, dated May 10, 1883 - (DCSO records, Vol. 21, Page 8760)

GLO survey by Norman D. Price, U.S. Surveyor, under Instructions dated Sept. 22, 1916 - (DCSO records Vol. 21 Page(s) 8851-52)

The standard cor. of Tp. 32 S., Rs. 7 and 8, is a Pine post 4 x 4 ins., 12" above ground, firmly set, marked and witnessed as described by the surveyor general. Alongside of post, Set a sandstone 18x14x8 ins., 14" in the ground, marked SC on N., with 6 grooves on N., E., and W. faces. The old bearing trees being dead and no suitable bearing trees available. Raise a mound of stone, 3 ft. base 1½ ft. high, N. of cor.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, W. Penley, crew - March 1968 - C.S. File 54/36-121

Found - Orig. 28" Pine, now stob, N.57°E., 33.9 ft.
 Orig. 36" Pine, now stob, N.20°W., 52.8 ft.
 Orig. 34" Fir, now stob, S.15°E., (Rec. S.20°E.) 40.9 ft.

Old stone set with 6 grooves on the N-E-W faces for corner. (Orig.??)

I find no good orig. evidence of this corner. However, by carefully chaining between the closing corner of S1|S6 T33S R7 and 8 W, which is 417.1 ft. and find the trees of the right type and size hitting good for bearing and distance. Set Brass cap at cor. mkd:

County Surveyors Office			
R	T 32 S	R	
8	<u>S 36 S 31</u>	7	
W	S 1	W	
T33S			
1968			

(Cont. Next Page)

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 100100

PRIMARY CORNER DESCRIPTION SW. Cor. Sec. 31 (Tsp Cor)

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

New BTs -6" S.Pine West, 2.0 ft. mkd. S36 CS BT.
6" S.Pine N.60°E., 17.5 ft. mkd. S31 CS BT.
10" Y.Pine S.13°E., 37.5 ft. mkd. T33S R8W S1 CS BT.