

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 100300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19 & 30; 24 & 25, T32-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16, 1881 (DCSO records Vol 20 Pg 8708)

Set a Fir post, 4½ ft. long, 4" sq., 18" in the ground, marked T32S R7W S19 on NE. face, S30 on SE. face, S25 on SW. face, T32S R8W S24 on NW. face; for the corner to secs. 19, 24, 25 and 30, from which

A Fir 16" dia. bears N.16°E., 37 lks. mkd. T32S R7W S19 BT
A Fir 20" dia. bears S.30°E., 84 lks. mkd. T32S R7W S30 BT
A Laurel 5" dia. bears S.35°W. 19 lks. mkd. T32S R8W S25 BT
A Pine 28" dia. bears N.6°W., 35 lks. mkd. T32S R8W S24 BT

Fd. and used in GLO survey by Dickerson, under Contract #474, dated May 1883 - (DCSO records, Vol. 21 Pages 8784-85)

NF - DCSO J.Powell - 12/1967 (added 10/2016) C.S. 54/36-161

Survey by Max Hull, L.S. #901 - For: Gregory Forest Products October 1990 - C.S. File 63/115 and M 111-4

Set 5/8" x 30" Iron rod with cap mkd. "Hull RS 901".

BTs - 8" Fir S.62°W., 7.20 ft.
6" Fir S.54°E., 6.90 ft.
7" Madrone N.16°E., 17.90 ft.
10" Fir N.04°W., 45.60 ft.

Corner falls on blazed line running West and North/South, blazed line bears East, 15 ft.

Fd. Ok by Jerry Estabrook, 4/2003 - C.S. File 65/45-24

BLM Dependent resurvey by Arthur R. Rambo, Cadastral Surveyor under Group No. 2179, surveyed July/Nov. 2007 - (DCSO records, Vol. 55 Page(s) 21601)

The cor. of secs. 19, 24, 25, & 30, reestablished by proportionate measurement by Hull, in 1990. There is no remaining evidence of the original cor., therefore this point is accepted as the cor.; monumented with an iron rod, 5/8" dia., firmly set, projecting 6" above the ground, with a yellow plastic cap mkd. HULL . RS 901, from which bearing trees mkd. by Hull, in 1990:

A madrone, 9" dia., bears N.16°E., 17.8 ft., with scribe marks S19 RS 901 in upper blaze, and BT in lower blaze.

A fir, 9" dia., bears S.63¼°E., 6.9 ft., with a healed double blaze.

A fir, 10" dia., bears S.56½°W., 6.9 ft., with a healed double blaze.

continued next page

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 100300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19 & 30; 24 & 25, T32-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A fir, 12" dia., bears N.3½°W., 45.5 ft., with a healed double blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, directly over iron rod, with brass cap mkd.

T 32 S
R 8 W R 7 W
S 24 | S 19
S 25 | S 30
2007

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Ron Quimby - Crew: J. Leonard and N. Fromdahl - 11/2013 - C.S. File 65/80-61

Found - BLM brass cap
10" madrona, N.16°E., 17.8 ft. vis. scribes.
12" fir S.63°E., 6.9 ft. healed blaze.
12" fir S.56°W., 6.9 ft. healed blaze.
14" fir N.4°W., 45.5 ft. healed blaze.
New - Set alum. post 2.0 ft west.
Re-tag trees
Note - Area burnt 8/2013.
Dec. 15°