

PRIMARY CORNER DESCRIPTION Sec. Cor. for 18 & 19; 13 & 24, T32-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 20 Page(s) 8709)

Set a Laurel post 4½ ft. long, 4" sq., 18" in the ground, marked T32S R7W S18 on NE. face; S19 on SE. face; S24 on SW. face; R8W S13 on NW. face; for the corner to Secs. 13, 18, 19 and 24, from which

- A Laurel 10" dia., bears N.30°E., 81 lks. dist., mkd. T32S R7W S18 BT.
- A Laurel 5" dia., bears S.12°E., 51 lks. dist., mkd. T32S R7W S19 BT.
- A Fir 6" dia., bears S.55°W., 23 lks. dist., mkd. T32S R8W S24 BT.
- A Live Oak 6" dia., bears N.55°W., 81 lks. dist., mkd. T32S R8W S13 BT.

Fd. and used in GLO survey by Dickerson, Contract #474, dated May 1883 (DCSO records, Vol. 21 Page 8787)

GLO remonumentation by Hans W. Thielsen, under Group #350, Surveyed, Nov. 1958/July 1959 - (DCSO records Vol. 33 Page(s) 13659)

The Sec. cor., determined at record bearing and distance from the three remaining original bearing trees:

- A Madrone 16" dia., bears N.30°E., 81 lks. dist., no marks remaining on opened blaze.
- A Fir 24" dia., bears S.55°W., 23 lks. dist., with illegible scribe marks visible on an opened and burned blaze.
- A Live Oak 12" dia., bears N.55°W., 81 lks. dist., with scribe marks R8W S13 visible on opened blaze.

At the corner point

Set an iron post, 3 ft. long, 1 in. dia., 28 ins. in the ground, with brass cap marked

T 32 S
R 8 W R 7 W
S 13 S 18
S 24 S 19
1958

from which

- A Fir 18" dia., bears N.19°E., 85 lks. dist., mkd. T32S R7W S18 BT.
- A Fir 9" dia., bears S.70½°E., 54 lks. dist., mkd. T32S R7W S19 BT.
- A Fir 14" dia., bears S.72½°W., 75 lks. dist., mkd. T32S R8W S24 BT.

(Cont. Next Page)

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 100400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 18 & 19; 13 & 24, T32-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>A Fir 12" dia., bears N.74°W., 47 lks. dist., mkd. T32S R8W S13 BT.</p>
<p>Cor. Fd. and used in BLM resurvey by Roseberry and Aanrud, Group #'s 821 and 876, surveyed Aug. 1973/Oct. 1975 (DCSO records, Vol. 40 Page 15970)</p>
<p>Fd. and used in BLM resurvey by Roseberry and Aanrud, Group #'s 350 and 960, surveyed Aug/Sept. 1978 (DCSO records, Vol. 42 Pages 16501-02)</p>
<p>Found OK by J. Estabrook, Apr. 2003 - M142-2 & C.S. 65/45-27</p>
<p>BLM Dependent resurvey by Arthur R. Rambo, Cadastral Surveyor under Group No. 2179, surveyed July/Nov. 2007 - (DCSO records, Vol. 55 Page(s) 21603)</p> <p>-----</p> <p>The cor. of secs. 13, 18, 19, & 24, on the W. bdy. of the Tp., monumented with an iron post, 1" dia., firmly set, projecting 6" above the ground, with alum. cap (properly) mkd from which the remaining original bearing trees, reported by Roseberry and Aanrud</p> <ul style="list-style-type: none">A madrone, 14" dia., bears N.30°E., 49.5 ft., with no scribe marks visible on opened and burned blaze.A fir, 30" dia., bears S.55°W., 15.2 ft., with no scribe marks visible on partially healed blaze.A live oak, 14" dia., bears N.58¼°W., 50.2 ft., with scribe marks R8W S13 visible on partially healed blaze. <p>and BTs mkd. by Thielsen, reported by Roseberry and Aanrud</p> <ul style="list-style-type: none">A fir, 24" dia. bears N.17°E. 56.1 ft. with a healed blazeA fir, 24" dia. bears S.71½°E. 35.6 ft with a healed blazeA fir, 25" dia. bears S.71°W. 48.8 ft. with a healed blazeA fir, 26" dia., bears N.75½°W., 30.1 ft., with a healed blaze. (Record, 31.0 ft.)
<p style="text-align: right;">2</p>