

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 100440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 18; and 13, T32-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 20 Page(s) 8709-10)

Set a Fir post, 4 ft. long, 4" sq., 20" in the ground, mkd. ¼ S on W. side for the ¼ sec. cor., from which
A Live Oak 5" dia., bears S.65°E., 10 lks. dist., mkd. ¼ S BT.
A Fir 12" dia., bears N.80°W., 8 lks. dist., mkd. ¼ S BT.

BLM resurvey by Lynn M. Roseberry and Rollin D. Aanrud, Cadastral Surveyors, Under Group #'s 821 and 876, surveyed Aug. 1973/Oct. 1975 (DCSO records Vol. 40 Page(s) 15971)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2½" dia., 20" in the ground, and in a mound of stone, 2½ ft. base, to top, with brass cap mkd:
T 32 S
R 8 W ¼ R 7 W
S 13 S 18
1973

from which
A Fir 19" dia., bears N.80½°E., 36½ lks. dist., mkd. ¼ S18 BT.
A Live Oak 5" dia., bears S.25½°W., 20½ lks. dist., mkd. ¼ S13 BT.