

PRIMARY CORNER DESCRIPTION Sec. Cor. for 6 & 7; 1 & 12 of T32-8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 20 Page(s) 8711)

-----

Set a Cedar post 4½ ft. long, 4" in dia., 20" in the ground for the corner to secs. 1, 6, 7, and 12, marked T32S R7W S6 on NE. side; S7 on SE. side; S12 on SW. side; R8W S1 on NW. side; from which

- A Pine 45" dia., bears N.80°E., 6 lks. dist., mkd. T32S R7W S6 BT.
- A Pine 14" dia., bears S.50°E., 140 lks. dist., mkd. T32S R7W S7 BT.
- A Fir 22" dia., bears S.8°W., 66 lks. dist., mkd. T32S R8W S12 BT.
- A Fir 20" dia., bears N.45°W., 123 lks. dist., mkd. T32S R8W S1 BT.

---

Fd. and used in GLO survey by Dickerson, May 1883, (DCSO records, Vol. 21 Page 8791)

---

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, W. Penley, crew - April 1968 - C.S. File 54/36-110

-----

Found - Unrecorded 3/4" I.Pipe at sec. corner.  
 Orig. 22" D.Fir, now down, S.8°W., 43.5 ft., bark scribe visible, S R8W S12  
 Pine stump N.80°E., no evidence.

Set Brass cap at cor. mkd: County Surveyors Office

R	T 32 S	R
8	<u>S 1</u>   <u>S 6</u>	7
W	S 12   S 7	W

1968

New BTs -8" Laurel S.41°E., 4.4 ft. mkd. T32S R7W S7 CS BT.  
 12" D.Fir S.42°W., 19.5 ft. mkd. T32S R8W S12 CS BT.  
 10" D.Fir N.56°W., 14.0 ft. mkd. T32S R8W S1 CS BT.  
 12" D.Fir N.64°E., 38.0 ft. mkd. T32S R7W S6 CS BT.

---

Fd. and used in BLM resurvey by Roseberry and Aanrud, Group #'s 821 and 876, surveyed Aug. 1973/Oct. 1975 (DCSO records, Vol. 40 Page 15974) AND also by Roseberry and Aanrud in 1978, (DCSO records, Vol. 42 Page 16508)

---

Fd. OK, by Max Hull, Sept. 1989, C.S. File 63/24 and M 108-69

---

continued next page

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 6 & 7; 1 & 12 of T32-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Ron Quimby - Crew: J. Leonard & N. Fromdahl - 11/2013 - C.S.  
File 65/80-42

-----

Condition report only

Found - DCSO brass cap (properly mkd)  
20" Fir N.64°E 38.0, healed face.  
20" Fir N.56°W., 14.0, healed face.  
26" Fir S.42°W., 19.5, healed face.  
14" madrona S.41°E., 4.4, vis. scribes

Set - 6' alum. post 2.0 west.  
Re-tag trees

Note - Area burnt 7/2013  
Compass decl. 15°E.