

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 20 Page(s) 8712)

Set a Fir post 4 ft. long, 4" sq., 20" in the ground, marked 1/4 S cor., the 1/4 sec. cor., from which
A Fir 14" dia., bears S.55°E., 10 lks. dist., mkd. 1/4 S BT.
A Fir 14" dia., bears N.70°W., 10 lks. dist., mkd. 1/4 S BT.

Douglas Co. Surveyors Office - John M. Powell and crew - August 27, 1965 - C.S. File 49/91-13

Found - Orig. 14" now 22" Fir N.70°W., 6.6 ft., shows good bark scribing "1/4 S BT"
Orig. 14" now 22" Fir S.55°E., 6.6 ft., shows good scars.

Set Brass cap at cor. mkd: County Surveyors Office
T 32 S
R8W 1/4 S 1 | S 6 R7W
1965

Rescribe-22" Fir N.70°W., 6.6 ft. "1/4 S1 CS BT"

Douglas Co. Surveyors Office - Randall Smith, Stephen Flause; Sept. 25, 1996 - C.S. File 65/9-18

Found - 2 1/2" dia. brass cap on a 1 1/2" O.D. by 36" long iron pipe is found out of ground. (1965 DCSO)

Accessories Found -

14" now 24" dia. down D.Fir with a fully healed single blaze, no bark scribing visible, (a portion of lower trunk is covered up). Position of roots agrees well with record "N.70°W., 6.6 ft." O.B.T.

19" now 20" dia. 8 ft. high D.Fir stump with a fully healed single blaze, bears S.55°E., 6.6 ft. (agrees with rec.) O.B.T.

Monument Set -

1965 DCSO BC/IP is set at a position determined from O.B.T.'s. Brass cap stamping "reset 1996" is added, BC/IP protrudes 6" above ground. A 2 ft. dia. mound of stone is placed around base.

New Accessories -

48" dia. 5 ft. high D.Fir stump with an 8" boat spike set in top through BT tag, 1 ft. easterly of center. Boat spike is stamped "B02". Boat spike bears N.80°W., 12.0'

24" dia. 3 ft. high D.Fir stump with an 8" boat spike set in top, near center through a BT tag. Boat spike is stamped "B01". Boat spike bears N.55 1/2°E., 52.5 ft.

(Cont. Next Page)

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 100640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 6; and S1 of T32-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New Accessories continued -
4 inch "+" is chiseled at toe of northerly face of large rock outcrop, 3 ft. above ground, "+" bears S.58°W., 18.8 ft.

Note - Corner lies on a steep northwesterly slope. No ascribable trees in area around corner. Corner lies approx. N.25°E., 40 ft. from top of large rock outcrop.

Ron Quimby - 10/2013 - C.S. File 65/80-25

Found - 1965 DCSO brass cap (properly mkd)
48" fir stump, 5' high with boat spike N.80°W., 12.0 ft.

4" + in rock outcrop S.58°W., 18.8 ft.

20" D.Fir stump 8' high bears S.55°E., 6.6 ft.

New - Set alum. post 2.0 North & 2.0 west of cor.
Re-tag BTs

Note - Corner on steep north face 200'± south of middle Cr. Rd. Area burnt 7/2013
Compass decl. 15½°E.

BLM resurvey by Brandon G Courtright, Cadastral Surveyor, under Group No. 2754, surveyed May/July 2014 - (DCSO records, Vol. 58 page(s) 23368-9)

The ¼ sec. cor. of secs. 1 & 6, perpetuated by Powell, in 1965, further perpetuated by Smith, in 1996, monumented with an iron post, 1½" dia., firmly set, projecting 10" above ground, with brass cap (properly) mkd.

from which the remains of the original bearing trees

A charred fir snag, broken at 8 ft., 9" dia., bears S.55°E., 6.6 ft., no marks visible.

A charred root wad of a dead and down tree, 6 ft. long, bears N.70°W., 6.6 ft., no marks visible.

and the accessories mkd. by Smith

A charred fir stump, 4 ft. tall, 20" dia., bears N.55¾°E., 52.3 ft., measured to a boat spike projecting 2" above the top of the stump.

A rock outcrop bears S.58°W., 18.8 ft., measured to the center of a chiseled cross on the northerly face, with a white, red. and black painted target.

A charred fir stump, 3.5 ft. tall, 40" dia., bears N.77½°W., 12.3 ft., measured to a boat spike set flush in the top of the stump.

and new reference monuments

continued next page

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 100640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 6; and S1 of T32-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

An iron rod, 36" long, 5/8" dia., driven 33" in the ground for a reference monument, bears S.84°19'03"E, 19.97 ft., with alum. cap (properly) mkd. RM1 T32S R7W 19.97 FT TO COR 1/4 S6 2014 and an arrow pointing to the cor.

An iron rod, 36" long, 5/8" dia., driven 34" in the ground for a reference monument, bears S.65°12'00"W, 19.21 ft., with alum. cap (properly) mkd. RM2 T32S R8W 19.21 FT TO COR 1/4 S1 2014 and an arrow pointing to the cor.