

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 18 and 19

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO rec Vol. 21 Page 8759)

-----  
 Set a Fir post 4 ft. long, 4" sq., 18" in the ground marked 1/4 S on N. face, for the 1/4 sec. cor., from which:

- A Pine 20" dia., bears N.78°E., 76 lks. mkd. 1/4 S BT.
- A Live Oak 8" dia., bears S.89°W., 116 lks. mkd. 1/4 S BT.

BLM resurvey by Lynn M. Roseberry and Rollin D. Aanrud, Cadastral Surveyors, Under Group #'s 350 and 960, surveyed Aug/Sept. 1978 (DCSO records Vol. 42 Page(s) 16500)

-----  
 The 1/4 sec. cor., determined at record bearing and distance from the only remaining original bearing trees:

- A B.Oak 27" dia., bears S.89°W., 116 lks., with scribe marks 1/4 B visible on opened blaze. (Rec. Live Oak) and a bearing tree of which I have no record:

- A Fir 21" dia., bears N.54 1/2°E., 60 lks. dist., with scribe marks BT visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2" dia., 24" in the ground, with brass cap marked T 32 S R 7 W

1/4  $\frac{S\ 18}{S\ 19}$   
 1978

from which new bearing trees:

- A Fir 19" dia., bears N.71 1/4°W., 32 1/2 lks., mkd. 1/4 S18 BT.
- A Fir 20" dia., bears S.65°W., 59 lks., mkd. 1/4 S19 BT.

Jerry Estabrook - Bruce Webster - 4/2003 - C.S. File 65/45-21

-----  
 Found - 3 1/4" brass cap on 2" galv. iron pipe (BLM 1978)  
 Orig. B.Oak 26" (tall stump with rotten face) bears S.89°W., 76.6 ft.

- A 27" fir stump bears N.54°30'E., 39.6 ft.
- A 22" fir stump (healed face & slant cut top) bears N.71°15'W., 21.5 ft. (BLM 1978)
- A 19" fir stump (healed face & slant cut top) bears S.65°W., 38.9 ft. (BLM 1978)

- New -
- 5/8"x30" iron rod driven 28" deep bears N.45°W., 5.0 ft. With out cap.
  - 5/8"x30" iron rod driven 28" deep bears N.45°E., 5.0 ft. With out cap.
  - 5/8"x30" iron rod driven 28" deep bears S.45°E., 5.0 ft. With out cap.
  - 5/8"x30" iron rod driven 28" deep bears S.45°W., 5.0 ft. With out cap.

Cont.

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 18 and 19

Alias	Description

BLM Dependent resurvey by Arthur R. Rambo, Cadastral Surveyor under Group No. 2179, surveyed July/Nov. 2007 - (DCSO records, Vol. 55 Page(s) 21606-7)

The 1/4 sec. cor. of secs. 18 and 19, monumented with an iron post, 2½" dia., firmly set, projecting 8" above the ground, with brass cap (properly) mkd.

from which the remains of an original bearing tree reported by Roseberry and Aanrud

A rotted oak stump, size indeterminate, bears S.89°W., 76.6 ft., no marks visible.

and a bearing tree mkd. by person(s) unknown, reported by Roseberry and Aanrud

A sawed fir stump, 27" dia., bears N.54½°E., 39.6 ft., no marks visible.

and bearing trees mkd. by Roseberry and Aanrud

A sawed fir stump, 19" dia., bears S.65°W., 38.9 ft., with a healed blaze.

A sawed fir stump, 22" dia., bears N.71¼°W., 21.5 ft., with a healed blaze.

from which reference monuments set by Estabrook, in 2003

An iron rod, 5/8" dia., firmly set, projecting 2" above the ground, bears N. 45° E., 5.0 ft.

An iron rod, 5/8" dia., firmly set, projecting 2" above the ground, bears S.45°E., 5.0 ft.

An iron rod, 5/8" dia., firmly set, projecting 2" above the ground, bears S.45°W., 5.0 ft.

An iron rod, 5/8" dia., firmly set, projecting 2" above the ground, bears N.45°W., 5.0 ft.

and new bearing trees

A live oak, 13" dia. bears N.73°E., 22.8 ft. mkd. ¼ S18 BT

A fir, 14" dia., bears S.83°E., 45.9 ft., mkd. ¼ S19 BT.

The geographic position in (NAD 1983 (CORS 96)) of the 1/4 section corner of sections 18 and 19, as determined by a tie from a temporary GPS point, established utilizing dual frequency, carrier phase GPS receivers, and processed using the National Geodetic Survey's Online Positioning User Service (OPUS), is as follows:

Latitude: 42°46'57.78" N.

Longitude: 123°34'24.96" W.

Fd. BC & accessories per rec. 12/11/2013 - R. Quimby M167-8