

PRIMARY CORNER DESCRIPTION S C for Secs. 31 and 32 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 20 Page(s) 8705) (and Page 8752)

-----  
Set a Fir post, for the S cor. to secs. 31 and 32 viz., post 4½ ft. long, 4" sq., 20" in the ground, mkd. S C T32S R7W on N.; S32 on E.; and S31 on W.; 5 notches on the East and 1 on West sides, from which

A Sugar Pine 30" dia., bears N.12°E., 83 lks. dist., mkd. S C T32S R7W S32 BT.

A Sugar Pine 30" dia., bears N.20°W., 75 lks. dist., mkd. S C T32S R7W S31 BT.

A Fir 30" dia., bears S.35°W., 145 lks. dist., mkd. S C T33S R7W S6 BT.

GLO survey by Oscar F. Thiel, Deputy Surveyor, under Contract #729, dated Dec. 24, 1900 and special instructions dated Sept. 12, 1901 (DCSO records Vol. 21 Page(s) 9060-61)

-----  
The standard corner of secs. 31 and 32, which is a Fir post, mkd. and witnessed as described by the surveyor general. I built a mound of stone around the post, and as only the stump of 2 other bearing trees remain, I mark

A Fir 16" dia., bears N.1½°E., 84 lks. dist., mkd. T32S R7W S32 BT.

A Fir 18" dia., bears N.72°W., 110 lks. dist., mkd. T32S R7W S31 BT.

The third original BT is still standing.

Douglas Co. Surveyors Office - Frank Jones & crew - May 27, 1968 - C.S. File 54/36-183

-----  
Found - 16" now 26" D.Fir N.1½°E., 55.4 ft., open and show scribing.

18" now 28" D.Fir N.72°W., 72.6 ft., open and shows scribing, and bark scribed BT.

Set Brass cap at cor. mkd: County Surveyors Office

T32S R7W S 31 | S 32  
T33S R7W S 6

1968

New BTs -6" D.Fir N.17°E., 17.0 ft. scribed T32S R7W S32 SC CS BT.

8" D.Fir N.64°W., 11.4 ft. scribed T32S R7W S31 SC CS BT.

This corner lies 660 ft. East of top of ridge, running N and S. and 603.9 ft. West of closing corner to secs. 5 and 6.