

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 200140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 31 and 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 21 Page(s) 8752)

Set a Pine post 4 ft. long, 4" sq., 24" in the ground for the 1/4 sec. cor. mkd. 1/4 S on W. side, from which:
A Pine 40" dia., bears N.82°E., 30 lks. mkd. 1/4 S BT.
A Fir 24" dia., bears S.72°W., 80 lks. mkd. 1/4 S BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, W. Penley, crew - May 27, 1968 - C.S. File 54/36-172

Found - Orig. 40" Pine now 54" stump, N.82°E., 19.8 ft., no trace of scribing.
Orig. 24" now 32" D.Fir S.72°W., 52.8 ft., found bark scribing, S T

Set Brass cap at cor. mkd: County Surveyors Office
T 32 S R 7 W
1/4 S 31 | S 32
1968

New BTs -6" D.Fir N.85°E., 31.8 ft. mkd. 1/4 S32 CS BT.

14" Cedar N.84°W., 32.2 ft. mkd. 1/4 S31 CS BT.

This 1/4 cor. lies 10 ft. East of an old unused logging road and approx. 100 ft. East of a ridge top.

Daniel Baker - For: Weyerhaeuser Co. - 11/2017 - M174-4

Found - 2 1/2" Douglas Co brass cap "1968"
17" fir, N.85°E., 31.9' to center - 1968 Douglas Co BT (rec = N.85°E., 31.8')
48" pine stump, N.82°E., 22.7' to center - original BT (record -N.82°E. 30 lks)
44" fir, S72°W., 53.0' to center - original BT (record - S.72°W., 80 lks)
19" cedar, N.84°W., 32.0' to center - 1968 Douglas Co BT (record - N.84°W., 32.2')
New - 11" fir, S.10°E., 10.5' to nail side/center-scribed "1/4 S32 BT"
5 ft metal post alongside corner.