

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Sec. cor. for 29, 30, 31 and 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO recs Vol 21 Pgs 8752-53)

Set a Laurel post 4 ft. long, 4" sq., 22" in the ground for cor. to secs. 29, 30, 31 and 32 marked T32S R7W S29 on NE.; S32 on SE.; S31 on SW.; and S30 on NW.; faces, also 1 notch on S. and 5 notches on E. angles of same, from which:

A Fir 15" dia. bears N.20°E., 48 lks. mkd. T32S R7W S29 BT
A Fir 20" dia. bears S.65°E., 25 lks. mkd. T32S R7W S32 BT
A Fir 30" dia. bears S.55°W., 31 lks. mkd. T32S R7W S31 BT
A Laurel 10" dia. bears N.28°W. 31 lks mkd T32S R7W S30 BT

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, W. Penley, crew - March 1968 - C.S. File 54/36-117

Found - Orig. 24" now 25" D.Fir N.20°E., 31.7 ft., bark scribe visible, T32S RW BT
Orig. 30" now 32" D.Fir S.65°E., 16.5 ft., bark scribe visible, T32S R7W
Orig. 30" D.Fir now stob, S.55°W., 20.5 ft.
No trace of NW BT.

Set Brass cap at cor. mkd: County Surveyors Office
T 32 S R 7 W
S 30 | S 29
S 31 | S 32
1968

New BTs -16" D.Fir N.17°W., 19.2 ft. mkd. T32S R7W S30 CS BT
40" Pine S.82°W., 28.4 ft. mkd. T32S R7W S31 CS BT.

Reblaze and rescribe:

25" D.Fir N.20°E., 31.7 ft. mkd. T32S R7W S29 CS BT.
32" D.Fir S.65°E., 16.5 ft. mkd. T32S R7W S32 CS BT.

This corner lies approx. 40 ft. W. of large rock outcrop on top of small spur running West.

DCSO-GIS Corner visitation - 2/26/2004 - Typed: 2/10/2011 - C.S. File 67/33-1

Monument - 1.25" IP/BC
Comment - ok

Daniel Baker - For: Weyerhaeuser Co. - 11/2017 - M174-4

Found - 2½" Douglas Co. brass cap "1968"
28" fir, N.20°E., 31.7' to center - original BT (GLO rec = N.20°E., 48 lks)
36" fir, S.66°E., 16.5' to center - original BT (GLO rec = S.65°E., 25 lks)

continued next page

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Sec. cor. for 29, 30, 31 and 32

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

40" pine snag, S.83°W., 28.5' to center - Douglas Co
BT (county record = S.82°W., 28.4')
22" fir, N.17°W., 19.0' to center - Douglas Co BT
(county record = N.17°W., 19.2')
New - 7" fir, S.83°W., 27.1' to nail side/center - scribed
"T32SR7WS31 BT"
Set 5 foot metal post alongside corner.