

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 200240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 29 and 30

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 21 Page(s) 8755)

-----  
Set a Laurel post, 4 ft. long, 4" sq., 24" in the ground marked  $\frac{1}{4}$  S on W. side for the  $\frac{1}{4}$  sec. cor., from which  
A Fir 60" dia., bears S.40°E., 17 lks. mkd.  $\frac{1}{4}$  S BT.  
A Laurel 5" dia., bears S.53°W., 36 lks. mkd.  $\frac{1}{4}$  S BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, W. Penley, crew - March 1968 - C.S. File 54/36-122

-----  
Found - Orig. 50" now 50" D.Fir S.40°E., 11.2 ft., shows bark scribe,  $\frac{1}{4}$  S BT

No trace of 5" laurel, SW BT.

Set Brass cap at cor. mkd: County Surveyors Office  
T 32 S R 7 W  
 $\frac{1}{4}$  S 30 | S 29  
1968

New BT - 25" D.Fir S.80°E., 27.2 ft. mkd.  $\frac{1}{4}$  S30 CS BT.  
Other BT OK, tagged same.