

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19, 20, 29 and 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO recs Vol 21 Page 8755)

Set a Laurel post, 4 ft. long, 4" sq., 18" in the ground for the cor. to secs. 19, 20, 29 and 30 marked T32S R7W S20 on NE.; S29 on SE.; S30 on SW.; and S19 on the NW. faces, also two notches on S. and 5 on E. angles of same, from which
A Fir 36" dia., bears N.55°E., 70 lks. dist. mkd. T32S R7W S20 BT.
A Laurel 16" dia., bears S.15°E., 58 lks. dist., mkd. T32S R7W S29 BT.
A Laurel 14" dia., bears S.55°W., 38 lks. dist., mkd. T32S R7W S30 BT.
A Cedar 10" dia., bears N.5°W., 29 lks. dist., mkd. T32S R7W S19 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, crew - December 1967 - C.S. File 54/36-104

Found - Orig. 10" now 24" Cedar N.5°W., 19.1 ft., bark scribe visible "BT".
Orig. 16" now 22" Laurel S.15°E., 38.3 ft. burnt out
Orig. 14" now 16" Laurel S.55°W., 25.1 ft. burnt out
Orig. 36" D.Fir now burnt stump, N.55°E., 46.2 ft.

Set Brass cap at cor. mkd: County Surveyors Office

T 32 S R 7 W
S 19 | S 20
S 30 | S 29
1967

New BTs -30" D.Fir S.23°W. 26.4 ft scribed T32S R7W S30 CS BT
8" D.Fir N.56°W., 22.2 ft. mkd. T32S R7W S19 CS BT.
6" Live Oak N.71°E., 15.6 ft. scribed T32S R7W S20 CS BT.
12" D.Fir S.25°E. 26.5 ft scribed T32S R7W S29 CS BT

Cor. Fd. and used in BLM resurvey by Roseberry and Aanrud, under Group #'s 350 and 960, surveyed Aug/Sept. 1978 - (DCSO records, Vol. 42 Pages 16498-99)

Fd. OK, October 1990, M 111-4
Fd. OK, DCSO, Oct. 14, 1992, C.S. File 64/32-18

BLM Dependent resurvey by Arthur R. Rambo, Cadastral Surveyor under Group No. 2179, surveyed July/Nov. 2007 - (DCSO records, Vol. 55 Page(s) 21604)

The cor. of secs. 19, 20, 29, and 30, monumented with an iron post, 1¼" dia., firmly set, projecting 14" above CONT...

TOWNSHIP 32 RANGE 07 POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19, 20, 29 and 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

the ground, with brass cap (properly) mkd.
from which the remains of the orig. BTs reported by Roseberry
and Aanrud

A rotted fir stump, size indeterminate, bears N.58½°E.,
46.2 ft., no marks visible.

A hollow madrone, size indeterminate, bears S.11½°E., 38.3
ft., no marks visible.

A madrone stump hole, size indeterminate, bears S.48°W.,
25.1 ft., no marks visible.

A cedar, 29" dia., bears N.1°W., 19.1 ft., with scribe
marks BT visible on bark blaze.

and BTs mkd. by the Douglas County Surveyor's Office, in
1967, reported by Roseberry and Aanrud

A live oak, 8" dia., bears N.71°E., 15.5 ft., with
fragmentary scribe marks visible on partially healed
double blaze.

A fir, 21" dia., bears S.25°E., 26.4 ft., with a healed
double blaze.

A fir, 30" dia., bears S.22½°W., 26.4 ft., with a healed
double blaze.

A fir, 12" dia., bears N. 55½° W., 22.1 ft., with a healed
double blaze.